

Han Q 8/0 - GS - Metal



| Part number | 19 12 008 0502 |
|--------------------|-------------------------------------|
| Specification | Han Q 8/0 - GS - Metal |
| HARTING eCatalogue | https://b2b.harting.com/19120080502 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|-----------------------------|---|
| Series of hoods/housings | Han-Compact [®] |
| Type of hood/housing | Hood |
| Description of hood/housing | for Han-Compact [®] half cable gland for Han [®] Q 8/0 Crimp (max. 400 V), Han [®] Q17/0 and Han [®] Q Data RJ45 |

Version

| Size | Han-Compact [®] |
|----------------------|--|
| Version | Side entry |
| Cable entry | 1x M25 |
| Locking type | Single locking lever |
| Field of application | Hoods/Housings for higher EMC requirements |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|-------------|
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 12 |

Material properties

| Material (hood/housing) | Zinc die-cast |
|-------------------------|---------------|
| Surface (hood/housing) | Nickel plated |
| RoHS | compliant |
| ELV status | compliant |

Page 1 / 2 | Creation date 2022-01-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 19 12 008 0502 Han Q 8/0 - GS - Metal



Material properties

| China RoHS | e |
|--------------------------------------|---------------|
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel |
| | Lead |

Specifications and approvals

| Approvals | DNV GL |
|-----------------------------------|--|
| UL / CSA | UL 1977 ECBT2.E235076 UL 2237 PVVA2.E318390 CSA-C22.2 No. 182.3 ECBT8.E235076 CSA-C22.2 No. 182.3 PVVA8.E318390 |
| CE | Yes |
| Commercial data Packaging size | 1 |
| Net weight | ' 163.76 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |

Page 2 / 2 | Creation date 2022-01-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2