

## Han 32B-HSM-HC-QB-2xM32



Part number	19 30 032 0272
Specification	Han 32B-HSM-HC-QB-2xM32
HARTING eCatalogue	https://b2b.harting.com/19300320272

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> B
Type of hood/housing	Surface mounted housing
Туре	High construction

#### Version

Size	32 B
Version	Side entry
Cable entry	2x M32
Locking type	Double locking lever
Han-Easy Lock <sup>®</sup>	Yes
Field of application	Standard hoods/housings for industrial connectors

### **Technical characteristics**

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

#### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

Page 1 / 2 | Creation date 2022-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



#### Material properties

Material (locking)Polycarbonate (PC) Stainless steelColour (locking)RAL 7037 (dust grey)Material flammability class acc. to UL 94 (locking levers)V-0RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH SVHC substancesYesREACH SVHC substancesPotassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
Material flammability class acc. to UL 94 (locking levers)V-0RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYes
(locking levers)V-URoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYes
ELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYes
China RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYes
REACH Annex XVII substances Not contained   REACH ANNEX XIV substances Not contained   REACH SVHC substances Yes
REACH ANNEX XIV substances Not contained   REACH SVHC substances Yes
REACH SVHC substances Yes
REACH SVHC substances Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
California Proposition 65 substances Yes
California Proposition 65 substances Nickel Naphthalene

#### Specifications and approvals

1 11	
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes
Commercial data	
Packaging size	1
Net weight	866 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2