

Han 24B-HMC-asg1-LB-M25



| Part number | 19 30 224 1251 |
|--------------------|-------------------------------------|
| Specification | Han 24B-HMC-asg1-LB-M25 |
| HARTING eCatalogue | https://b2b.harting.com/19302241251 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|--------------------------|-------------------------|
| Series of hoods/housings | Han [®] HMC |
| Type of hood/housing | Surface mounted housing |
| Туре | Low construction |

Version

| Size | 24 B |
|----------------------------|---|
| Version | Side entry |
| Cable entry | 1x M25 |
| Locking type | Single locking lever |
| Han-Easy Lock [®] | Yes |
| Field of application | Special hoods and housings for high mating cycles |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|---|-------------|
| Mating cycles with other HMC components | ≥10,000 |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| Material (hood/housing) Aluminium die-cast |
|--|
|--|

Page 1 / 2 | Creation date 2022-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 19 30 224 1251 Han 24B-HMC-asg1-LB-M25



Material properties

eCl@ss

| Surface (hood/housing) | Powder-coated |
|--|---|
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate (PC) Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Naphthalene |
| Specifications and approvals | |
| Approvals | DNV GL |
| Commercial data | |
| Packaging size | 1 |
| Net weight | 319.9 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |

Page 2 / 2 | Creation date 2022-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

27440202 Shell for industrial connectors

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2