

Han-Eco Outdoor 16A HSM1-M20 w. cov./gl.



•	
Part number	19 46 316 0252
Specification	Han-Eco Outdoor 16A HSM1-M20 w. cov./gl.
HARTING eCatalogue	https://b2b.harting.com/19463160252

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Eco [®] A
Type of hood/housing	Surface mounted housing
Description of hood/housing	With thermo-plastic cover With integrated cable gland

Version

Size	16 A
Version	Side entry
Cable entry	1x M20
Locking type	Single locking lever

Technical characteristics

Limiting temperature	-40 +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP65
Clamping range	6 13 mm

Material properties

Material (hood/housing)	Polyamide (PA) Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	FPM
Colour (seal)	RAL 7001 (silver-grey)

Page 1 / 2 | Creation date 2022-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

Material (locking)	Polyamide (PA) Fibre-glass reinforced
Colour (locking)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0
Material flammability class acc. to UL 94 (locking levers)	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead

Specifications and approvals

eCl@ss

pecifications	IEC 61984
	EN 45545-2 R22: HL1, HL2, HL3
opecifications	EN 45545-2 R23: HL1, HL2, HL3
	EN 45545-2 R24: HL1, HL2, HL3
CE	Yes
Commercial data	
Commercial data	
Packaging size	1
Net weight	144.5 g
iter treight	· · · · · · · · · · · · · · · · · · ·
Country of origin	Germany
European customs tariff number	85389099

27440202 Shell for industrial connectors

Page 2 / 2 | Creation date 2022-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2