



Single connectors for fibre optical cables (POF²)

Identification	Part-Number	Drawing	Dimensions in mm
<p>FO connectors</p> <p>for 1 mm polymer fibre cable Ø 2.2 mm</p> <p>F-SMA type with hexagonal nut</p> <p>FH-ST type</p> <p>Versatile Link type</p> <p>Crimp</p> <p>Crimpless</p> <p>for 1 mm polymer fibre cable 3.6 mm SERCOS</p> <p>F-SMA type with hexagonal nut</p> <p>for 1 mm polymer fibre cable 6 mm SERCOS</p> <p>F-SMA type with hexagonal nut</p>	<p>20 10 001 1211</p> <p>20 10 001 2211</p> <p>20 10 001 7111</p> <p>20 10 001 7112</p> <p>20 10 001 1241</p> <p>20 10 001 1221</p>		<p>The connector for 1 mm POF² may be directly attached to the fibre by crimping, gluing or by using a "hot plate".</p> <p>Insertion loss: POF < 2.5 dB</p>
<p>F-TNC (IP 65)</p> <p>Male cable connector for 1 mm polymer fibre cable-type SERCOS Ø 6mm</p> <p>Female cable connector for 1 mm polymer fibre cable-type Ø 2.2 mm</p>	<p>20 10 001 6211</p> <p>20 10 001 6233</p>		<p>SERCOS = SEriell Realtime COmmunication System</p> <p>²⁾ POF = Polymer optical fibre</p>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Connectors](#) category:

Click to view products by [HARTING](#) manufacturer:

Other Similar products are found below :

[0004700001](#) [6100-R](#) [6313](#) [F709722200](#) [F709730000](#) [F718183204](#) [F727403500](#) [F727752800](#) [8119](#) [9440F20-27S-190](#) [944-120-6001](#)
[9441F10SL-3S](#) [9444W28-21S](#) [9444W36-10S](#) [9446W20-16S](#) [953-101-5310-P](#) [954-101-57202B](#) [A0270169](#) [12-9122](#) [12-5702](#) [AX101713](#)
[AX102420](#) [AX103923](#) [AX104024](#) [AX104193](#) [AX104230](#) [AX104562](#) [AX105203-B25](#) [AX105205-S1](#) [EHSC2M](#) [17-300800](#) [181-011-126](#)
[181-011-S](#) [181-057-126](#) [NKSOPBUY](#) [20500002116](#) [2064996-1](#) [20800001065](#) [2170](#) [9132](#) [2612](#) [2620](#) [9291](#) [9440F16-10S](#) [9440F20-18S](#)
[9444W32-73S](#) [9446F16-10S-190](#) [953-106-50231](#) [953-120-5003](#) [955-120-5110](#)