



Ha-VIS RFID RF-R3x0 Reader

Advantages

- Designed for the harsh industrial environment
- Tested according industry and railway standards
- Ready for software customisation
- M12 connectors
- Power over Ethernet
- Ha-VIS Middleware compatible: RF-R300
- OPC UA for AutoID Companion specification: RF-R310
- Modbus/TCP communication: RF-R320
- GS1® ALE 1.1 based Middleware included: RF-R350

General description

- The Ha-VIS RF-R3x0 is a very robust industry and railway approved RFID reader. It is tested according the EN 50 155.
- All components are designed for a very long lifetime in harsh industrial environments.
- The modular software design of the new reader gives HARTING the ability to support various communications protocols such as LLRP, OPC UA, or even the implementation of a very powerful middleware functionality based on ALE 1.1 standard of the GS1®. In addition, customer-specific variants can be supplied.

Technical characteristics

Transponder protocol	EPC Class 1 Gen2 (ISO 18000-6c)
UHF RFID antenna interface	
Antenna connection	2 x RP-TNC connector (50 Ohm); reader internally multiplexed
Output power	max. 0.5 W
Frequency range	865 ... 928 MHz (region configurable)
Interfaces	
Diagnosis (LED)	3 LEDs to visualise the device and antenna status
Inputs / Outputs	up to 8 configurable IOs (not available in PoE operation)
Performance	
Bulk-reading capability	up to 100 transponders/s
Max. reading distance	up to 5 meters, related to the transponder type and environmental conditions
Protocol	
	RF-R300: LLRP (Low Level Reader Protocol, worldwide standardised)
	RF-R310: OPC UA according to OPC Unified Architecture for AutoID Companion specification
	RF-R320: Modbus/TCP for an easy PLC connection
	RF-R350: Embedded middleware functionality based on the GS1® ALE 1.1 standard
	– Web services
	– http telegrams
	– TCP telegrams
	– UDP telegrams
	– MySQL database support
	– MQTT
Power supply	
Power supply	24 V DC (± 5 %) / Power over Ethernet (PoE)
Current consumption	max. 500 mA
Operating system	Linux (Kernel 3.x.x)
System performance	1 GHz ARM processor 1 GB RAM 4 GB eMMC up to 32 GB flash (via Micro SD Card)



Ha-VIS RFID RF-R3x0 Reader

Technical characteristics

Design features

Material of housing	aluminium
Dimensions (W x H x D)	132 x 104 x 35 mm
Installation on DIN rail	DIN rail mounting kit (optional accessories)

Environmental conditions

Operating temperature	-40 °C ... +55 °C
Storage temperature	-40 °C ... +85 °C
Relative humidity	5 % ... 95 % (non-condensing)
Vibration	EN 60 068-2-6 10 Hz to 150 Hz: 0.075 mm / 1g
Shock	EN 60 068-2-27 Acceleration: 30 g
Protection class	IP67

Technical characteristics

Norms & safety

Radio license	EN 302 208 FCC 47 FCR Part 15 IC RSS-GEN, RSS-210
EMC	EN 301 489
Low voltage	EN 60 950
Human exposure	EN 50 364
RoHS compliant	

Railway (rolling stock)

EMC	EN 50 121-3-2
Vibration	EN 61 373 Cat. 1B
Shock	EN 61 373 Cat. 1B
Wet heat (cyclic)	EN 50 155 / EN 60068-2-30
Fire protection	EN 45545-2

Identification	Part number	Drawing	Dimensions in mm
Ha-VIS RFID RF-R300 EU/FCC	20 91 105 1101		
Ha-VIS RFID RF-R310 EU/FCC (OPC UA)	20 91 105 1211		
Ha-VIS RFID RF-R320 EU/FCC (Modbus TCP)	20 91 105 1311		
Ha-VIS RFID RF-R350 EU/FCC (ALE 1.1 Middleware tested acc. to railway standards)	20 91 105 1111		
Software update ALE 1.1 for RF-R3x0	26 99 400 0000 02		
Optional accessories			
DIN rail mounting kit	20 95 200 0004		
Wall mounting kit	20 95 300 0007		
M12 X-coded Ethernet cable (2 m)*	09 47 841 1002		
M12 A-coded cable assembly (2 m)* (IOs / ext. power supply)	21 34 840 0C79 020		
Ha-VIS Coax TNC/TNC-RP, H155 PVC, 3 m*	20 93 204 0121		
Ha-VIS eCon 3060BT-A-P	24 03 006 0020		



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Sub-GHz Modules](#) category:

Click to view products by [HARTING](#) manufacturer:

Other Similar products are found below :

[HMC-C024](#) [nRF24L01P-MODULE-SMA](#) [CMD-KEY2-418-CRE](#) [V640-A90](#) [SM1231E868](#) [HMC-C582](#) [SM-MN-00-HF-RC](#) [HMC-C031](#)
[LoRa Node Kit\(US\)](#) [Sierra HL7588 4G KIT\(US\)](#) [WISE-4610-S672NA](#) [EC21AUFA-MINIPCIE](#) [EC21EUGA-MINIPCIE](#) [CS-EASYSWITCH-](#)
[25](#) [EC21JFB-MINIPCIE](#) [E28-2G4M27S](#) [DL-RFM95-868M](#) [DL-RFM95-915M](#) [DL-RFM96-433M](#) [Ra-07H-V1.1](#) [Ra-07](#) [Ra-01SH](#) [Ra-01S-T](#)
[Ra-01SH-T](#) [CMD-HHCP-418-MD](#) [CMD-HHCP-433-MD](#) [CMD-HHLR-418-MD](#) [2095000000200](#) [XB9X-DMRS-031](#) [20911051101](#) [COM-](#)
[13909](#) [HMC-C033](#) [COM-13910](#) [WRL-14498](#) [SX1276RF1KAS](#) [HMC-C004](#) [HMC-C011](#) [HMC-C014](#) [HMC-C010](#) [HMC-C050](#) [HMC-C001](#)
[HMC-C006](#) [HMC-C029](#) [HMC-C030](#) [HMC-C019](#) [HMC-C021](#) [HMC-C041](#) [HMC-C042](#) [HMC-C048](#) [HMC-C051](#)