

M8-Screw-3P-F-ANG



| Part number | 21 02 359 4301 |
|--------------------|-------------------------------------|
| Specification | M8-Screw-3P-F-ANG |
| HARTING eCatalogue | https://b2b.harting.com/21023594301 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|---------------|------------------------|
| Series | Circular connectors M8 |
| Element | Cable connector |
| Specification | Angled |

Version

| Termination method | Screw termination |
|--------------------|-------------------|
| Gender | Female |
| Shielding | Unshielded |
| Number of contacts | 3 |
| Coding | A-coding |
| Locking type | Screw locking |

Technical characteristics

| Conductor cross-section | 0.09 0.5 mm² |
|-------------------------|--------------------|
| Conductor cross-section | AWG 28 AWG 20 |
| Rated current | 4 A |
| Rated voltage | 60 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulation resistance | >10 ⁸ Ω |
| Contact resistance | ≤10 mΩ |

Page 1 / 3 | Creation date 2022-01-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Technical characteristics

| Tightening torque | 0.4 Nm |
|---|-----------------------|
| Wrench size (knurled screw / knurled nut) | 13 |
| Ambient temperature | -30 +85 °C |
| Mating cycles | ≥100 |
| Degree of protection acc. to IEC 60529 | IP67 locked condition |
| Cable diameter | 4 5.5 mm |
| Isolation group | I (600 ≤ CTI) |

Material properties

| Material (insert) | Polyamide (PA) |
|--------------------------------------|--|
| Material (contacts) | Brass |
| Surface (contacts) | Au over Ni Mating side |
| Material (hood/housing) | Polyamide (PA) Copper-zinc alloy |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 0d7d3693-d625-47ab-934a-d241bf72c86e |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |

Specifications and approvals

| Specifications | IEC 61076-2-104 |
|--------------------------------|-----------------|
| | |
| Commercial data | |
| Packaging size | 1 |
| Net weight | 16.4 g |
| Country of origin | Czechia |
| European customs tariff number | 85366990 |

Page 2 / 3 | Creation date 2022-01-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 21 02 359 4301 M8-Screw-3P-F-ANG



Commercial data

eCl@ss

27440102 Circular connector (for field assembly)

Page 3 / 3 | Creation date 2022-01-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-0054130014002613001500991-3637-600-52051612618210368364148R4006A16M0101R3006A20M00541-4001142-0000642-010154-22279-44-22281-14-22284-943-0011343-0120341-4001342-0000843-0102643-0116243-0117343-10000XS3P-M421-2600X518050X8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-1621343-01338XS2RD4265XS2R-D426-1XS8A-0441859RD04-103R004860RD04-113R004860RD04-213R0041-213245-2