

WDF M12-F-M16x1,5-A kod.-4po-m.Litze 500



Part number	21 03 311 2400
Specification	WDF M12-F-M16x1,5-A kod4po-m.Litze 500
HARTING eCatalogue	https://b2b.harting.com/21033112400

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Circular connectors M12
Element	Panel feed through
Specification	With conductors for front mounting

Version

Gender	Female
Shielding	Unshielded
Number of contacts	4
Coding	A-coding
Locking type	Screw locking
Pack contents	incl. lock nut

Technical characteristics

Conductor cross-section 0.5 mm² Conductor cross-section AWG 20 Rated current 4 A Rated voltage 250 V Rated impulse voltage 1.5 kV		
Rated current 4 A Rated voltage 250 V Rated impulse voltage 1.5 kV	Conductor cross-section	0.5 mm ²
Rated current 4 A Rated voltage 250 V Rated impulse voltage 1.5 kV	Conductor cross-section	AWG 20
Rated voltage 250 V Rated impulse voltage 1.5 kV	Conductor cross-section	AVVO 20
Rated impulse voltage 1.5 kV	Rated current	4 A
Rated impulse voltage 1.5 kV		
	Rated voltage	250 V
	Rated impulse voltage	1.5 kV
Pollution degree 3	Pollution degree	3
Overvoltage category III	Overvoltage category	III
Cronolizado category	o volvollago calogoly	
Insulation resistance $>10^8 \Omega$	Insulation resistance	>10 ⁸ Ω



Technical characteristics

Contact resistance	≤10 mΩ
Tightening torque	2 Nm Lock nut
Ambient temperature	-40 +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP67 mated condition
Isolation group	I (600 ≤ CTI)
Conductor length	50 cm

Material properties

Material (insert)	Polyamide (PA)
Material (contacts)	Brass
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead Naphthalene

Specifications and approvals

Specifications	IEC 61076-2-101
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079

Commercial data

Packaging size	1
Net weight	30 g

Product data sheet 21 03 311 2400 WDF M12-F-M16x1,5-A kod.-4po-m.Litze 500



Commercial data

Country of origin	Germany
European customs tariff number	85444290
eCl@ss	27440103 Sensor-actuator connector chassis (sensor technology acc.)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 1-3637-600-5205 1612618 21036836414 8R4006A16M010 1R3006A20M005 41-40011 42-00006 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01203 41-40013 42-00008 43-00343 43-01026 43-01162 43-01173 43-10000 XS3P-M421-2 600X518050X 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-16213 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004 860RD04-113R004 860RD04-213R004 1-213245-2