

M12 PCB receptacle female b-coded 5pol.



•	
Part number	21 03 341 2518
Specification	M12 PCB receptacle female b-coded 5pol.
HARTING eCatalogue	https://b2b.harting.com/21033412518

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Circular connectors M12
Element	PCB adapter
Specification	Straight

Version

Termination method	Reflow soldering termination (THR)
Gender	Female
Shielding	Shielded
Number of contacts	5
Coding	B-coding
Details	Order housings separately
Pack contents	60 pieces in a tray

Technical characteristics

Rated current	4 A
Rated voltage	50 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Overvoltage category	III
Insulation resistance	>10 ⁸ Ω
Contact resistance	≤10 mΩ
Ambient temperature	-40 +85 °C

Page 1 / 2 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Technical characteristics

Mating cycles	≥100
Isolation group	I (600 ≤ CTI)
Material properties	
Material (insert)	Liquid crystal polymer (LCP)
Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead Naphthalene

Specifications and approvals

Specifications	IEC 61076-2-101
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079

Commercial data

Packaging size	60
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27460201 PCB connector (board connector)

Page 2 / 2 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-0054130014002613001500991-3637-600-52051612618210368364148R4006A16M0101R3006A20M00541-4001142-0000642-010154-22279-44-22281-14-22284-943-0011343-0120341-4001342-0000843-0102643-0116243-0117343-10000XS3P-M421-2600X518050X8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-1621343-01338XS2RD4265XS2R-D426-1XS8A-0441859RD04-103R004860RD04-113R004860RD04-213R0041-213245-2