

# M12 slim angled female A-cod 5-pol



Part number	21 03 821 4505
Specification	M12 slim angled female A-cod 5-pol
HARTING eCatalogue	https://b2b.harting.com/21038214505

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Connectors
Series	Circular connectors M12
Identification	Slim Design
Element	Cable connector
Specification	Angled

# Version

Termination method	Crimp termination
Gender	Female
Shielding	Shielded
Number of contacts	5 4
Coding	A-coding
Locking type	Screw locking
Details	Please order crimp contacts separately.

# **Technical characteristics**

Conductor cross-section	0.13 0.82 mm²
Conductor cross-section	AWG 26 AWG 18
Wire outer diameter	≤2.3 mm
Rated current	4 A
Rated voltage	48 V AC 60 V DC
Rated voltage	110 V AC/DC when used with 4 contacts

Page 1/3 | Creation date 2022-01-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany

Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



### Technical characteristics

Rated impulse voltage	1.5 kV
Pollution degree	3
Overvoltage category	III
Insulation resistance	>10 <sup>8</sup> Ω
Contact resistance	≤10 mΩ
Tightening torque	0.6 Nm
Wrench size (knurled screw / knurled nut)	15
Ambient temperature	-40 +85 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	5.7 8.8 mm
Isolation group	I (600 ≤ CTI)

### Material properties

Material (insert)	Polyamide (PA)
Material (hood/housing)	Zinc die-cast
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
	Nickel
California Proposition 65 substances	Lead Naphthalene

#### Specifications and approvals

Specifications	IEC 61076-2-101
UL / CSA	UL 2238 CYJV2.E302521
	CSA-C22.2 No. 182.3 CYJV8.E302521

# Commercial data

Packaging size	1
Net weight	50 g

Page 2 / 3 | Creation date 2022-01-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



### Commercial data

Country of origin

European customs tariff number

eCl@ss

Romania

85366990

27440102 Circular connector (for field assembly)

Page 3 / 3 | Creation date 2022-01-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-0054130014002613001500991-3637-600-52051612618210368364148R4006A16M0101R3006A20M00541-4001142-0000642-010154-22279-44-22281-14-22284-943-0011343-0120341-4001342-0000843-0102643-0116243-0117343-10000XS3P-M421-2600X518050X8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-1621343-01338XS2RD4265XS2R-D426-1XS8A-0441859RD04-103R004860RD04-113R004860RD04-213R0041-213245-2