

M12-L male crimp A-coded 5pole



Part number	21 03 822 1535
Specification	M12-L male crimp A-coded 5pole
HARTING eCatalogue	https://b2b.harting.com/21038221535

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Circular connectors M12
Identification	INOX
Element	Cable connector
Specification	Straight

Version

Termination method	Crimp termination
Gender	Male
Shielding	Shielded
Number of contacts	4 5
Coding	A-coding
Locking type	Screw locking
Details	Please order crimp contacts separately.

Technical characteristics

Conductor cross-section	0.14 0.75 mm²
Conductor cross-section	AWG 26 AWG 18
Wire outer diameter	≤2.3 mm
Rated current	4 A
Rated voltage	60 V
Rated impulse voltage	1.5 kV

Page 1 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Technical characteristics

Pollution degree	3
Overvoltage category	III
Insulation resistance	>10 ⁸ Ω
Contact resistance	≤10 mΩ
Tightening torque	0.6 Nm
Wrench size (knurled screw / knurled nut)	17
Ambient temperature	-40 +85 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	4.5 8.8 mm
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	Polyamide (PA)
Material (hood/housing)	Stainless steel
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
	Lead Naphthalene

Specifications and approvals

Specifications	IEC 61076-2-101
Commercial data	
Packaging size	1
Net weight	54.6 g
Country of origin	Germany
European customs tariff number	85366990

Page 2 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 21 03 822 1535 M12-L male crimp A-coded 5pole



Commercial data

eCl@ss

27440102 Circular connector (for field assembly)

Page 3 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-0054130014002613001500991-3637-600-52051612618210368364148R4006A16M0101R3006A20M00541-4001142-0000642-010154-22279-44-22281-14-22284-943-0011343-0120341-4001342-0000843-0102643-0116243-0117343-10000XS3P-M421-2600X518050X8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-1621343-01338XS2RD4265XS2R-D426-1XS8A-0441859RD04-103R004860RD04-113R004860RD04-213R0041-213245-2