

# PFT M12 crimp shielded A-cod.4pol.female



Part number 21 03 822 2425

Specification PFT M12 crimp shielded Acod.4pol.female

HARTING eCatalogue https://b2b.harting.com/21038222425

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	Circular connectors M12
Element	Cable connector Panel feed through
Specification	for rear mounting

#### Version

Termination method	Crimp termination
Gender	Female
Shielding	Shielded
Number of contacts	4
Coding	A-coding
Locking type	Screw locking
Details	Please order crimp contacts separately.

#### Technical characteristics

Conductor cross-section	0.14 0.75 mm²
Conductor cross-section	AWG 26 AWG 18
Wire outer diameter	≤2.3 mm
Rated current	4 A
Rated voltage	250 V
Rated impulse voltage	1.5 kV
Pollution degree	3

This product is not orderable anymore. Please contact your local distribution partner.



#### Technical characteristics

Overvoltage category	III
Insulation resistance	>10 <sup>8</sup> Ω
Contact resistance	≤10 mΩ
Tightening torque	2 Nm Lock nut
Ambient temperature	-40 +85 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	4.5 8.8 mm
Isolation group	I (600 ≤ CTI)

## Material properties

Material (insert)	Polyamide (PA)
Material (hood/housing)	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead Naphthalene

#### Specifications and approvals

Specifications	IEC 61076-2-101
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079

### Commercial data

Packaging size	10
Net weight	43.7 g

Page 2 / 3 | Creation date 2022-01-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany
Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

Product data sheet 21 03 822 2425 PFT M12 crimp shielded A-cod.4pol.female

This product is not orderable anymore. Please contact your local distribution partner.



#### Commercial data

Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440102 Circular connector (for field assembly)

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 1-3637-600-5205 1612618 21036836414 8R4006A16M010 1R3006A20M005 41-40011 42-00006 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01203 41-40013 42-00008 43-00343 43-01026 43-01162 43-01173 43-10000 XS3P-M421-2 600X518050X 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-16213 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004 860RD04-113R004 860RD04-213R004 1-213245-2