

M12-SD-CC-CRIMP-8P-YCOD-F-STR-SHLD



Part number	21 03 861 2805
Specification	M12-SD-CC-CRIMP-8P-YCOD-F-STR- SHLD
HARTING eCatalogue	https://b2b.harting.com/21038612805

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Circular connectors M12
Identification	Power
Element	Cable connector
Specification	Straight

Version

Termination method	Crimp termination
Gender	Female
Shielding	Shielded
Number of contacts	8
Coding	Y-coding
Locking type	Screw locking
Details	Please order crimp contacts separately.
Details	For Fast Ethernet applications only

Technical characteristics

Rated current	6 A
Rated voltage	50 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Rated current (data)	0.5 A
Overvoltage category	III



Technical characteristics

Insulation resistance	>10 ⁸ Ω
Contact resistance	≤10 mΩ
Tightening torque	0.6 Nm
Wrench size (knurled screw / knurled nut)	17
Ambient temperature	-40 +85 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	5.7 8.8 mm
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	Polyamide (PA)
Material (hood/housing)	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Specifications and approvals

Specifications	IEC 61076-2-113

Commercial data

Packaging size	1
Net weight	45 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440102 Circular connector (for field assembly)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below:

600X518037X MA1EAF1200 6STD15PCR99B70A 8R4000A16M020 8R4A00A18M020 8R5000A16M005 1200910008 1200910011 1300140094 130203-0054 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-01016 41-40011 41-40017 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00002 43-01166 41-40005 41-40016 43-00161 43-01191 XS3P-M421-2 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R4006A16A120 8R4000A16M010 RKC 50/16 1R3004A20A1201 6-22279-3 N03FA03144 1300140077 XS8A-0441 859RD04-103R004 860RD04-113R004 860RD04-213R004 860-X08-213R004 1-213245-2 2273142-2