

## M12-L male 4-p D-cod. with conduit M17x1



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 21 03 882 1411  |
| Specification      | M12-L male 4-p D-cod. with conduit M17x1  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/21038821411">https://b2b.harting.com/21038821411</a> |

### Identification

|               |                          |
|---------------|--------------------------|
| Category      | Connectors               |
| Series        | Circular connectors M12  |
| Element       | Cable connector          |
| Specification | with conduit<br>Straight |

### Version

|                    |   |
|--------------------|---|
| Termination method | Crimp termination                       |
| Gender             | Male                                    |
| Shielding          | Shielded                                |
| Number of contacts | 4                                       |
| Coding             | D-coding                                |
| Locking type       | Screw locking                           |
| Details            | Please order crimp contacts separately. |
| Details            | For Fast Ethernet applications only     |

### Technical characteristics

|                         |                               |
|-------------------------|-------------------------------|
| Conductor cross-section | 0.14 ... 0.75 mm <sup>2</sup> |
| Conductor cross-section | AWG 26 ... AWG 18             |
| Wire outer diameter     | ≤2.3 mm                       |
| Rated current           | 4 A                           |
| Rated voltage           | 48 V AC<br>60 V DC            |
| Rated impulse voltage   | 1.5 kV                        |



Pushing Performance

## Technical characteristics

|   |                              |
|---|------------------------------|
| Pollution degree                          | 3                            |
| Transmission characteristics              | Cat. 5 Class D up to 100 MHz |
| Overvoltage category                      | III                          |
| Data rate                                 | 10 Mbit/s<br>100 Mbit/s      |
| Insulation resistance                     | $>10^8 \Omega$               |
| Contact resistance                        | $\leq 10 \text{ m}\Omega$    |
| Tightening torque                         | 0.6 Nm                       |
| Wrench size (knurled screw / knurled nut) | 17                           |
| Ambient temperature                       | -40 ... +85 °C               |
| Mating cycles                             | $\geq 500$                   |
| Degree of protection acc. to IEC 60529    | IP65 / IP67 mated condition  |
| Cable diameter                            | 4.5 ... 8.8 mm               |
| Isolation group                           | I ( $600 \leq \text{CTI}$ )  |

## Material properties

|                                      |  |
|--------------------------------------|--|
| Material (insert)                    | Polyamide (PA)   |
| Material (hood/housing)              | Zinc die-cast  |
| RoHS                                 | compliant with exemption                               |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50   |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Yes  |
| REACH SVHC substances                | Lead   |
| ECHA SCIP number                     | 0d7d3693-d625-47ab-934a-d241bf72c86e                   |
| California Proposition 65 substances | Yes  |
| California Proposition 65 substances | Nickel<br>Lead<br>Naphthalene                          |

## Specifications and approvals

|                |                 |
|----------------|-----------------|
| Specifications | IEC 61076-2-101 |
|----------------|-----------------|



Pushing Performance

## Specifications and approvals

|          |                                   |
|----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E102079             |
|          | CSA-C22.2 No. 182.3 ECBT8.E102079 |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 48 g   |
| Country of origin              | Germany  |
| European customs tariff number | 85366990   |
| eCl@ss                         | 27440102 Circular connector (for field assembly) |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular Metric Connectors](#) category:*

*Click to view products by [HARTING](#) manufacturer:*

Other Similar products are found below :

[600X518037X](#) [6STD15PCR99B70A](#) [8R4000A16M020](#) [8R5000A16M005](#) [1200910002](#) [1203580030](#) [1200910008](#) [1200910011](#) [1300140094](#)  
[130203-0054](#) [1300140026](#) [1300150099](#) [1-3637-600-5205](#) [1612618](#) [21036836414](#) [8R4006A16M010](#) [1R3006A20M005](#) [41-40011](#) [42-00006](#)  
[42-01015](#) [4-22279-4](#) [4-22281-1](#) [4-22284-9](#) [43-00113](#) [43-01203](#) [41-40013](#) [42-00008](#) [43-00343](#) [43-01026](#) [43-01162](#) [43-01173](#) [43-10000](#)  
[XS3P-M421-2](#) [600X518050X](#) [8R5006A16M020](#) [8R5006A16M005](#) [8R4000A16M010](#) [6-22279-3](#) [1605332](#) [N03FA03144](#) [1300140077](#) [43-](#)  
[16213](#) [43-01338](#) [XS2RD4265](#) [XS2R-D426-1](#) [XS8A-0441](#) [859RD04-103R004](#) [860RD04-113R004](#) [860RD04-213R004](#) [1-213245-2](#)