

M12 MD PP IDC CC Male Straight 8Pol Xcod



Part number	21 12 283 1830
Specification	M12 MD PP IDC CC Male Straight 8Pol Xcod
HARTING eCatalogue	https://b2b.harting.com/21122831830

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors	
Series	Circular connectors M12	
Identification	PushPull	
Element	Cable connector	
Specification	Straight	
Version		
Termination method	IDC termination	

Gender	Male
Shielding	Shielded
Number of contacts	8
Coding	X-coding
Locking type	Outer PushPull

Technical characteristics

Wire outer diameter	0.9 1.6 mm
Rated current	0.5 A
Rated impulse voltage	0.8 kV
Pollution degree	3
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz
Overvoltage category	III
Data rate	10 Gbit/s
Insulation resistance	>10 ⁸ Ω

Page 1 / 3 | Creation date 2024-07-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Technical characteristics

Contact resistance	≤10 mΩ
Limiting temperature	-40 +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	5.7 8.8 mm
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	PA66
Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

Specifications and approvals

Specifications	IEC 61076-2-109
Specifications	acc. to IEC 61076-2-010

Commercial data

Packaging size	1
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140819863
ETIM	EC002635

Page 2 / 3 | Creation date 2024-07-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Commercial data

eCl@ss

27440116 Circular connector (for field assembly)

Page 3 / 3 | Creation date 2024-07-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

600X518037X 8R5000A16M005 1-3637-600-5205 1545399 1A4000-348 8R5006A18A120 1R3006A20M005 1R3006A20M030 RF-12P1N8A80DU RF-12P1N8A90DU 41-01016 4-22279-4 4-22281-1 4-22284-9 41-40005 XS3P-M421-2 SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 7A3006-32 1R3004A20A1201 N03FA03144 1406328 XS2RD4265 080804EMF00000 XS2R-D426-1 XS8A-0441 2273142-2 41-50000 41-50002 ASB 8-S3064/5 M 43-02534 MA1LKE1700 1400943 8R4006A16M020 WR8U26E02C300 8R5000A16M020 1R3000A20M050 884A30K05M006 1200910005 1201010003 2168083-2 RC-Z2062 SACC-MSQ-M12MS-25-3 2 SCO SACC-E-FSB-5CON-M16/0 5 SC SACC-DSI-FS-4CON-PG9/2 0UL SACC-1/2 NPT-LOCKNUT BEDC854NN0000052A000 BKUA854NN0086155A000 T4145515021-002