

M12 PFT Crimp 8-pole x-coded female 1m



Part number	21 33 080 0850 010
Specification	M12 PFT Crimp 8-pole x-coded female 1m
HARTING eCatalogue	https://b2b.harting.com/21330800850010

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Circular connectors M12
Identification	PushPull
Element	Panel feed through
Specification	Pre-assembled on one side Industrial Ethernet cable (4x 2x AWG 26/7) for rear mounting
Version	
Cable length	1 m
Ŭ	1.111
Gender	Female
Gender	Female
Gender Shielding	Female Shielded
Gender Shielding Core structure	Female Shielded 4x 2x AWG 26/7
Gender Shielding Core structure Number of contacts	Female Shielded 4x 2x AWG 26/7 8

Technical characteristics

Rated current	0.5 A
Rated voltage	50 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz

Page 1/3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany

Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Technical characteristics

Overvoltage category	III
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Insulation resistance	>10 ⁸ Ω
Contact resistance	≤10 mΩ
Tightening torque	2 Nm Lock nut
Wrench size	18
Ambient temperature	-40 +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	Liquid crystal polymer (LCP)
Material (contacts)	Brass
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Page 2 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Specifications and approvals

Specifications	IEC 61076-2-109
Commercial data	
	1
Packaging size	
Net weight	96 g
Country of origin	Romania
European customs tariff number	85444290
eCl@ss	27440103 Sensor-actuator connector chassis (sensor technology acc.)

Page 3 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Cables / Actuator Cables category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

6096360964M83513/19-F01CP703000D02F2002703001D02F0602703001D02F300704000D02F120773032K02F030802027107404-1802027213811-1804001A09M150805001A09M050284914-023584914-0237885030A09M0208R4J30E03C30031200651332120065171312006608441200660845120066117312006800711200720053120072008112007200991200720217120080023112008601251200870123120098010212006502671200650298120066018312006607821200660849120066129512006612971200661342120066134312006702801200670220120068033112007202521200730184120086034412008703591200870643120098000812009800311210502211120050211120068033112007202521200730184120086034412008703591200870643