



C1 HAR-FLEX 68 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WHITE LABEL

FLAT CABLE,UL2678,AWG30.68CORE

C2 HAR-FLEX 68 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
67	AWG 30	67
68	AWG 30	68

HARTING P/N	Cable length(L)
3315 243 010 0122	100 ± 3
3315 243 020 0122	200 ± 5
3315 243 050 0122	500 ± 10

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE & LOT INFORMATION
HARTING P/N & REVISION

	All rights reserved Department HCS - CN	All Dimensions in mm Original Size DIN A3		Scale 1.5:1	Free size tol.	Ref. \
		HARTING Customised Solutions D-32339 Espelkamp	Created by ZHENGL	Inspected by WANGE	Standardisation CHENJU	Date 2018-10-12
Title Har-Flex 68Pole,Dul-end,With SR,L=XXMM						Doc-Key / ECM-Nr. 100586962/UGD/000/A 50000014.1225
		Type TB	Number 33150023		Rev. A	Page 1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ribbon Cables / IDC Cables](#) category:

Click to view products by [HARTING](#) manufacturer:

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [cab-LVDV-PWR-10-15](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#) [NM-2J2-051-PS1-JJAB](#) [1700/14SF \(100FT\)](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [119-885](#) [318-818](#) [318-818-25](#) [318-818-50](#) [DS1057-06A282R-30.5](#) [DS1057-09A282R-30.5](#) [DS1057-12A282R-30.5](#) [DS1057-14A282R-76.5](#) [DS1057-20A282R-76.5](#) [DS1057-30A282R-76.5](#) [DS1057-34A282R-76.5](#) [DS1057-40A282R-76.5](#) [DS1057-60A282R-76.5](#) [DS1057-64A282R-76.5](#) [DS1058-08M28-30.5](#) [DS1058-30M28-30.5](#) [3750/10 \(100FT\)](#) [0015712](#) [0015905](#) [S30109](#) [11203](#) [11223](#) [11243](#) [11262](#) [0037147](#) [0022512](#) [0022412](#)