



**C1**  
HAR-FLEX 80 POLE FEMALE CONNECTOR  
WITH STRAIN RELIEF

**C2**  
HAR-FLEX 80 POLE FEMALE CONNECTOR  
WITH STRAIN RELIEF

**WIRING TABLE**

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
79	AWG 30	79
80	AWG 30	80

HARTING P/N	Cable length(L)
3315 243 010 0123	100 ± 3
3315 243 020 0123	200 ± 5
3315 243 050 0123	500 ± 10

**NOTES:**

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE  
HARTING P/N

	All rights reserved		Created by ZHENGL		Inspected by WANGE		Standardisation CHENJU		Date 2018-10-12		State Final Release	
	Department HCS - CN		Title Har-Flex 80 Pole,Dul-end,With SR,L=XXMM		Type TB		Number 33150024		Doc-Key / ECM-Nr. 100586986/UGD/000/A 50000014.1226		Rev. A Page 1/1	
All Dimensions in mm Original Size DIN A3			Scale 1.5:1		Free size tol.		Ref. \		Sub. \			
HARTING Customised Solutions D-32339 Espelkamp												

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Ribbon Cables / IDC Cables](#) category:*

*Click to view products by [HARTING](#) manufacturer:*

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [cab-LVDV-PWR-10-15](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-GNM-2J2-051-PS1-JJAB](#) [1700/14SF \(100FT\)](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [119-885](#) [318-818](#) [318-818-25](#) [318-818-50](#) [DS1057-06A282R-30.5](#) [DS1057-09A282R-30.5](#) [DS1057-12A282R-30.5](#) [DS1057-14A282R-76.5](#) [DS1057-20A282R-76.5](#) [DS1057-30A282R-76.5](#) [DS1057-34A282R-76.5](#) [DS1057-40A282R-76.5](#) [DS1057-60A282R-76.5](#) [DS1057-64A282R-76.5](#) [DS1058-08M28-30.5](#) [DS1058-30M28-30.5](#) [3750/10 \(100FT\)](#) [0015712](#) [0015905](#) [S30109](#) [11203](#) [11223](#) [11243](#) [11262](#) [0037147](#) [0022512](#) [0022412](#)