

F+B Hybridcbl. f/- st/- 7.5m



Part number	33 50 300 0140 075
Specification	F+B Hybridcbl. f/- st/- 7.5m
HARTING eCatalogue	https://b2b.harting.com/33503000140075

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Series	Han [®] F+B
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	Female Hood
Type of cable	Hybrid cable (copper/copper)
Version	
Cable length	7.5 m
Number of cores	13
Core structure	2x 2x AWG 22 2x 0.75 mm ² 2x 1.5 mm ² 5G 2.5 mm ²
Number of contacts	12
Number of data contacts	4
Number of signal contacts	4
Number of power contacts	4
PE contact	Yes

Technical characteristics	
Rated current (signal)	10 A
Rated voltage (signal)	250 V

Page 1 / 2 | Creation date 2021-12-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com

Product data sheet 33 50 300 0140 075 F+B Hybridcbl. f/- st/- 7.5m



Technical characteristics

Rated impulse voltage (signal)	4 kV
Pollution degree (signal)	3
Rated current (power)	20 A
Rated voltage (power)	400 V
Rated impulse voltage (power)	6 kV
Pollution degree (power)	3
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +90 °C unmoved -30 +90 °C moved
Degree of protection acc. to IEC 60529	IP69
Cable diameter	16.5 mm
Minimum bending radius	10x Cable diameter (repeated bending)

Material properties

Material (cable)	Polyolefin copolymer
Colour (cable)	Black

Specifications and approvals

Approvals	Ecolab Topactive 200
	Ecolab Topactive 500
	Ecolab Topax 66
	Ecolab Topax 990
	Ecolab Topactive OKTO

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85444290
eCl@ss	27060311 Assembled sensor actuator-line

Page 2 / 2 | Creation date 2021-12-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Cables / Actuator Cables category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

6096360964M83513/19-F01CP703000D02F2002703001D02F0602703001D02F300704000D02F120773032K02F030802027107404-1802027213811-1804001A09M150805001A09M050284914-023584914-0237885030A09M0208R4J30E03C30031200651332120065171312006608441200660845120066117312006800711200720053120072008112007200991200720217120080023112008601251200870123120098010212006502671200650298120066018312006607821200660849120066129512006612971200661342120066134312006702801200670220120068033112007202521200730184120086034412008703591200870643120098000812009800311210502211120050211120068033112007202521200730184120086034412008703591200870643