



Advantages

- All hardware and software components included to start your industrial condition monitoring application in under 10min
- Built and Tested in accordance to industry transportation standards for the harshest conditions
- Embedded non-proprietary vendor agnostic, open dynamic, scalable future proof middleware software stack architecture
- Robust, adaptable, upgradeable hardware
- IP-rated Industrial connectors
- Power over Ethernet 48 V PoE or 12/24 V DC for quick network deployment
- Integration of IP and non-IP devices creating an open best of breed architecture at the edge level

General description

- MICA is an extremely robust IoT edge computer hardware/software that is engineered and designed to meet the standards, and requirements for critical infrastructures in Data Centers, Automation, Oil & Gas, Industrial Automation, Facilities, and Healthcare environments. MICA is tested in accordance to IP67 standards providing a modular world class hardware chassis.
- MICA hardware components are carefully engineered for an extensive life cycle in critical and harsh environments where reliability and uptime are crucial.
- MICA modular hardware and software design enables IoT architects, Integrators, development engineers and end-users, to unleash their systems potential. This is accomplished through a powerful blend of a web-based non-proprietary open source architecture.
- MICA applications include, Asset Tracking, Condition Monitoring/Control, and System Integration-Digital Retrofits/migrations of proprietary protocols.
- The BOSCH "Connected Industrial Sensor Solution" (CISS) boasts 8 different environmental sensors in one: temperature, humidity, accelerometer, pressure, light, acoustic, gyroscope, and a magnetometer.

Technical characteristics (MICA)

System performance	1 GHz ARM processor 1 GB RAM 4 GB eMMC up to 32 GB Flash (via Micro SD Card)
Interfaces	Ethernet (TCP/IP) 10/100 Mbit/s; Full Spec. 802.3 2 USB A Push-Pull
Inputs / Outputs	up to 8 configurable IOs (12 / 24 V)
Power supply	
Power supply	12/24 V DC ($\pm 5\%$) / Power over Ethernet (PoE)
Current consumption	max. 500 mA
Diagnosis (LED)	2 LEDs to visualize the device status
Protocol	Embedded middleware functionality 1.1 standard <ul style="list-style-type: none"> – Web services – http telegrams – TCP telegrams – UDP telegrams – MySQL database support – MQTT
Operating system	Linux (Kernel 3.x.x)
Design features	
Material of housing	corpus: Aluminum, powder coated front cover: fiberglass reinforced high performance plastic
Dimensions (W x H x D)	132 x 86 x 35 mm
Installation on DIN rail	DIN rail mounting kit (see optional accessories)
Environmental conditions	
Operating temperature	-25 °C ... +75 °C
Storage temperature	-25 °C ... +85 °C
Relative humidity	5 % ... 95 % (non-condensing)
Vibration	EN 60 068-2-6 10 Hz to 150 Hz: 0.075 mm / 1 g
Shock	EN 60 068-2-27 Acceleration: 30 g
Norms & safety	
EMC	EN 301 489
Low voltage	EN 60 950
Human exposure	EN 50 364
RoHS compliant	
Railway	tested according to EN 50155 (Q2 2016)

HARTING MICA® CISS Complete IIoT Starter Kit - Data Sheet



Description	Part number	Drawing	Dimensions in mm
<p>HARTING MICA CISS Complete IIoT Starter Kit</p> <p><u>Kit Components:</u></p> <p>HARTING IIC MICA USB</p> <p>M12 X coded PushPull cable assembly,1m</p> <p>M12 Cable Assembly A-cod st/- m/- 1,0m</p> <p>BOSCH "Connected Industrial Sensor Solution" (CISS)</p> <p>HARTING USB PushPull CISS-cable</p> <p>12V, 1A Power Supply</p>	<p>73460000007</p> <p>2095000000200</p> <p>09488223756010</p> <p>21348400C79010</p>		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Networking Modules](#) category:

Click to view products by [HARTING](#) manufacturer:

Other Similar products are found below :

[SE305-T](#) [509FX-SC](#) [SE308-T](#) [FCOPPER-SFP-100](#) [BNDL-MWF](#) [75060R-40](#) [301-2010-27](#) [DC-ES-4SB-EU](#) [MGM111E256V2](#)
[LTP5901IPC-IPRB1C1#PBF](#) [LTP5901IPC-IPRC1C2#PBF](#) [LTP5901IPC-IPRC1C1#PBF](#) [LTP5901IPC-IPRB1C2#PBF](#) [LTP5901IPC-](#)
[IPRA1C2#PBF](#) [112011-5033](#) [VSMD001V072](#) [65440R](#) [2000000844](#) [2000000849](#) [BB-WSW2C00015-1](#) [WISE-1020-0C01E](#) [WISE-1020-](#)
[0S01E](#) [WISE-1021WR-1100E](#) [RAPID-NI-V2005](#) [RAPID-NI-V2007](#) [RAPID-NI-V2009](#) [RAPID-NI-V2011](#) [RAPID-NI-V2012](#) [RAPID-NI-](#)
[V2105](#) [RAPID-NI-V2107](#) [RAPID-NI-V2108](#) [RAPID-NI-V2109](#) [RAPID-NI-V2112](#) [855-19619](#) [X2E-Z1C-W1-W](#) [X2E-Z4C-D2-A](#) [PuIM-](#)
[1G4T-I211-BP-R10](#) [PuIM-1G4T-I211-R10](#) [PUZZLE-IN003B-C0/8G-R10](#) [XXV710DA2OCP2](#) [MO11AA003-01R](#) [WP20010NMK-01](#)
[WP500100S-01](#) [XP1001000-05R](#) [XP1001000M-05R](#) [XP1002000-05R](#) [XP100200S-05R](#) [XPD1001000-01](#) [XPP100200S-02R](#) [112113-0001](#)