

Customer Information Sheet

DRAWING No.: M80-700XXX

SHEET 2 OF 2

IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

ORDER CODE:

M80-700XXX

TOTAL No. OF CONTACTS:

27, 36, 45, 51, 63

FINISH:

05 = 100% GOLD

22 = SELECTIVE GOLD + TIN/LEAD

42 = SELECTIVE GOLD + 100% TIN

NOTES:

1. FROM No. 1 POSITION, CONTACTS NUMBERED IN SEQUENCE FROM RIGHT TO LEFT AND FROM BOTTOM ROW TO TOP ROW.

SPECIFICATION:

MATERIAL:

MOULDING = POLYAMIDE 46 UL94V-0, BLACK

CONTACT = PHOSPHOR BRONZE

JACKSCREWS = STAINLESS STEEL

FINISH:

05 = 0.25 - 0.3µ 100% GOLD

22 = 0.75µ GOLD ON CONTACT AREA, 3.0µ 90/10 TIN/LEAD ON TAILS

42 = 0.75µ GOLD ON CONTACT AREA, 3.0µ 100% TIN ON TAILS

ELECTRICAL:

CURRENT RATING AT 25°C = 3.0A MAX

CURRENT RATING AT 85°C = 2.2A MAX

VOLTAGE PROOF = 360V AC/DC

CONTACT RESISTANCE (INITIAL) = 20 MILLIOHMS MAX

CONTACT RESISTANCE (AFTER CONDITIONING) = 25 MILLIOHMS MAX

INSULATION RESISTANCE (INITIAL) = 1,000 MEGOHMS MAX

INSULATION RESISTANCE (AFTER CONDITIONING) = 100 MEGOHMS MIN

MECHANICAL:

DURABILITY = 500 OPERATIONS

MAXIMUM INSERTION FORCE = No. OF CONTACTS x 2.8N

MAXIMUM WITHDRAWAL FORCE = No. OF CONTACTS x 1.8N

MINIMUM WITHDRAWAL FORCE = No. OF CONTACTS x 0.2N

ENVIRONMENTAL:


TEMPERATURE RANGE = -55°C TO +125°C

PACKING:

TRAYS

FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C017XX (LATEST ISSUE)


(NO. OF CONTACTS PER ROW x 2.00) + 13.10 MAX



(NO. OF CONTACTS PER ROW x 2.00) + 7.00

NO. OF PITCHES PER ROW x 2.00

NO. 1 CONTACT (SEE NOTE 1)



No. 1 CONTACT

6.20 MAX

SECTION A-A


M2.5 JACKSCREW

Ø0.50 TYP

WASHER

M2.5 NUT

2.00 TYP



NO. OF PITCHES PER ROW x 2.00

(NO. OF CONTACTS PER ROW x 2.00) + 7.00

RECOMMENDED PC BOARD LAYOUT

SM	9	15.06.10	10832
NAME	ISS.	DATE	C/NOTE
APPROVED: S. MCCULLAGH			
CHECKED: R. ADDE			
DRAWN: A. LIOTTA			
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE

S/AREA: mm²

TITLE: 3-ROW 2mm PITCH CONNECTOR, MALE, STRAIGHT THROUGHBOARD P.C. TAIL

DRAWING NUMBER:

M80-700XXX

SHT

2 OF 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Harwin](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-](#)
[5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-](#)
[367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)