



SMD 3.0X3.0 CERAMIC SEAM SEAL PACKAGE
PRODUCT FEATURES

- Small size 3.0x3.0x1.25mm
- Welding can be done with Auto-SMD
- Low-loss SAW component
- Low amplitude ripple
- Sharp rejections at both out-bands
- RoHS compliant

PRODUCT PHOTO

PRODUCT SPECIFICATIONS

Item		Specifications	Unit
Frequency Range	f_c	100~3600MHz	MHz
Standard Frequency		1575.42, 1582.4, 1568, 2655	MHz
Useful Band Width		3,25,48 or specify	MHz
Insertion Loss (min)	IL	0.9,1.3,1.8, 2.2 or specify	dB
VSWR(max)		2.0	dB
Operating Temperature Range		-40~+85	°C
Storage Temperature Range		-40~+85	°C

PACKAGE OUTLINE / DIMENSIONS


Pin No.	Description
2	Input
5	Output
1,3,4,6	Ground

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Resonators](#) category:

Click to view products by [HCI](#) manufacturer:

Other Similar products are found below :

[B39431R820H210](#) [ECS-HFR-40.00-B-TR](#) [CSTLS4M00G53Z-A0](#) [ECS-HFR-20.00-B-TR](#) [CSTNE16M0V510000R0](#)
[CSTNE14M7V510000R0](#) [CSTNE8M00GH5C060R0](#) [DJ2032K768C5T8188X01](#) [KZA20000](#) [KZA107](#) [HCTB1-1.000-CRBHRL](#) [AWSZT-3.58CP-T4](#) [SF33M6-836.500-F25IL28AL](#) [SRD11-315.000-F75IL22AL](#) [SR21S4-433.920-F75IL18AL](#) [SF11S5-915.000-F26IL02AL](#)
[SR32M4-433.920-F75IL25AL](#) [SRTO39-316.800-F75IL13AL](#) [HCTB1-455.000-CRBEL](#) [KZA24000](#) [KZT6000](#) [KZA8000](#) [KZA169344](#)
[KZT2350](#) [KZT169344](#) [KF143392](#) [KZA4000](#) [KTOR423](#) [KUM20950](#) [KZB455E](#) [KZA16000](#) [KZT16000](#) [KZT4190](#) [KZA12000](#) [KZA3640](#)
[KZT10000](#) [KD143392](#) [KZT20000](#) [KTO43392](#) [KZA2000](#) [KZA5000](#) [KZT3640](#) [KZT12000](#) [KZB460E](#) [KZA6000](#) [KSF465B](#) [KD1R3150](#)
[KTOR3150](#) [KZT8000](#) [KSF455K](#)