



SECTION A-A

Rating :  
 5A 250V AC T105 UL cUL  
 2.5A 250V AC VDE 3C KC  
 Insert And Extract Force: 1.36kgf~6.8kgf  
 Terminal Strength:  $\geq 80N$   
 Operating Life:  $\geq 5000$  cycles  
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min  
 terminals to Base: 3750V AC (50-60Hz) 1min  
 Leakage Current : 1mA  
 Insulation Resistance:  $\geq 100M\Omega$  500V DC  
 Body Materil: NYLON 66 94V-0

A4				普通公差									
A3				COMMON TOLERANCE :									
A2				UP TO 5	$\pm 0.20$	单位	mm	投影		品名	Ac Inlet C6型	比例	Free
A1				ABOVE 5 TO 30	$\pm 0.30$	UNIT		PROJECTED		PRODUCT NAME			
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	$\pm 5^\circ$	绘图	黄旭程	核对		型号	DB-6		
						日期	2014.10.20	核准		料号	DB-6-4VS2S8(G)		
						DATE		APPROVAL BY		PART NO.			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Connectors](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[B04P-VL-VN-1.8](#) [1600206-1](#) [163-0308-EX](#) [163-4012-EX](#) [163-4117-EX](#) [163-7421](#) [163-MJ22-EX](#) [171-0721-EX](#) [KLDX-SMT-0202-BPTR](#)  
[163-0179-EX](#) [163-1000-EX](#) [163-4007-EX](#) [163-4015-EX](#) [171-0722-E](#) [171-7391](#) [K596](#) [KLD-0201-BC](#) [KPPX-D](#) [4C6831AX](#) [TS3PNJ](#)  
[E16550-0008](#) [VLP-08V-1](#) [VLP-12V-1](#) [VLS-01V](#) [DC PLUG-P1M-P1MR](#) [09442](#) [AS120-M](#) [09760](#) [CP30240](#) [TAMIYA-M](#) [TAMIYA-MT1](#)  
[TAMIYA-MT2](#) [4840.1200](#) [4840.2202](#) [C5080HI-04P-18 + C5080HI-C](#) [JC-138](#) [JC-210](#) [JPO-25 \(FC6814\)](#) [JYO-26 \(FC6811\)](#) [JYO-29](#)  
[\(FC68102\)](#) [KLBPS 3](#) [KLS 10 SCHWARZ](#) [KLS 40 SCHWARZ](#) [KPJXHT-4S](#) [DC-10A FC68148](#) [DC-10B \(FC68149\)](#) [WKLS 2](#) [WKLS 40](#)  
[FA67555](#) [XNES/J 210 SCHWARZ](#) [XNES/J 250 SCHWARZ](#)