



PANEL THICKNESS:1.0~1.5mm  
PANEL HOLE SIZE

Rating : **10A 250V AC 3C**  
 Insert And Extract Force: 1.36kgf~6.8kgf  
 Operating Life:  $\geq 5000$  cycles  
 Withstand Voltage: Between all terminals:2000VAC (50-60Hz)1min  
 terminals to Base:3750V AC (50-60Hz)1min  
 Leakage Current : 1mA  
 Insulation Resistance:  $\geq 100M\Omega$  500V DC  
 Body Materil: NYLON 66 94V-2-0

A4				普通公差							
A3				COMMON TOLERANCE :							
A2				UP TO 5	±0.20	单位	mm	投影		品名	Ac Outlet
A1				ABOVE 5 TO 30	±0.30	绘图	黄旭程	核对		型号	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	日期	2015. 8. 25	核准	料号	PART NO.	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Connectors](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[163-0308-EX](#) [163-4012-EX](#) [163-4117-EX](#) [163-MJ22-EX](#) [171-0721-EX](#) [KLDX-SMT-0202-BPTR](#) [163-0179-EX](#) [163-4015-EX](#) [171-0722-E](#)  
[K596](#) [KLD-0201-BC](#) [4C6831AX](#) [LCB60PW-M](#) [LCB60PB-M](#) [LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#) [LCB40PW-M](#)  
[LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCB30-F](#) [LCC40-M](#) [LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#)  
[513820200](#) [DC-S014A-D025-20A](#) [DC007B-2.5-J](#) [DC005-2.5](#) [DC005-2.5-T](#) [DC-S019A-D025-10A](#) [DC007B-2.0](#) [DC-018-2.5A-2.5](#) [DC-005-](#)  
[A25](#) [DC-005-A20](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#) [DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-](#)  
[130](#)