



**SPECIFICATIONS**

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 50V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material:PBT,UL94V-0

编 号	尺寸 (mm)	
	A	B
HC-1.0-2Y	1.00	5.00
HC-1.0-3Y	2.00	6.00
HC-1.0-4Y	3.00	7.00
HC-1.0-5Y	4.00	8.00
HC-1.0-6Y	5.00	9.00
HC-1.0-7Y	6.00	10.00
HC-1.0-8Y	7.00	11.00
HC-1.0-9Y	8.00	12.00
HC-1.0-10Y	9.00	13.00
HC-1.0-11Y	10.00	14.00
HC-1.0-12Y	11.00	15.00
HC-1.0-13Y	12.00	16.00
HC-1.0-14Y	13.00	17.00
HC-1.0-15Y	14.00	18.00
HC-1.0-16Y	15.00	19.00

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 Mapping 2013.07.01	钱岳生			料号 PART NO. HC-1.0-NY	版本 REV. A			
			X.±0.25	X.*±2°		审核 Audit 张名 2013.07.03	品名 TITLE 1.0孔座	页次 SHEET 1/1					
			.X±0.20	.X*±1°							核准 Approved 张名 2013.07.05	客户料号 CUTM. NO.	
			.XX±0.15	.XX*±0.5°									
.XXX±0.10	.XXX*±0.5°	深圳市华灿天禄电子有限公司											

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)  
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)  
[001000](#)