



SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $100\text{M}\Omega$ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-1.25-2A	1.25	4.25
HC-1.25-3A	2.50	5.50
HC-1.25-4A	3.75	6.75
HC-1.25-5A	5.00	8.00
HC-1.25-6A	6.25	9.25
HC-1.25-7A	7.50	10.50
HC-1.25-8A	8.75	11.75
HC-1.25-9A	10.00	13.00
HC-1.25-10A	11.25	14.25
HC-1.25-11A	12.50	15.50
HC-1.25-12A	13.75	16.75
HC-1.25-13A	15.00	18.00
HC-1.25-14A	16.25	19.25
HC-1.25-15A	17.50	20.50
HC-1.25-16A	18.75	21.75

PCB LAYOUT

联系电话 18058866958

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	HC-1.25-NA		版本 REV.	A			
			X.±0.25	X.'±2'		审核 CHECK	2013、07、01		品名 TITLE	1.25开口直针		页次 SHEET	1/1		
			.X±0.20	.X'±1'			2013、07、03			WAFER DIP TYPE					
			.XX±0.15	.XX'±0.5'			张名			客户料号 CUTL NO.					
.XXX±0.10	.XXX'±0.5'	核准 APPROVAL	2013、07、05		张名		深圳市华灿天禄电子有限公司								
单位 UNITS			MM	比例 SCALE	1:1										

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)
[001000](#)