



**SPECIFICATIONS**

- 1、Current Rating: 9A AC, DC
- 2、Voltage Rating: 600V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1500V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-5557-2*1AW		5.40
HC-5557-2*2AW	4.20	9.60
HC-5557-2*3AW	8.40	13.80
HC-5557-2*4AW	12.60	18.00
HC-5557-2*5AW	16.80	22.20
HC-5557-2*6AW	21.00	26.40
HC-5557-2*7AW	25.20	30.60
HC-5557-2*8AW	29.40	34.80
HC-5557-2*9AW	33.60	39.00
HC-5557-2*10AW	37.80	43.20
HC-5557-2*11AW	42.00	47.40
HC-5557-2*12AW	46.20	51.60

**PCB LAYOUT**

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	HC-5557-2*NA		版本 REV.	A		
			X.±0.25	X.'±2'		2013、07、01	品名 TITLE		双排弯针			页次 SHEET	1/1	
			.X±0.20	.X'±1'					2013、07、03	客户料号 CUTL. NO.				
			.XX±0.15	.XX'±0.5'										
			.XXX±0.10	.XXX'±0.5'	核准 APPROVAL	张名	2013、07、05	深圳市华灿天禄电子有限公司						
					单位 UNITS	MM	比例 SCALE	1:1						

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)  
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)  
[800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#) [803-43-024-10-001000](#)