



**SPECIFICATIONS**

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon6T, UL94V-0  
PIN Phosphoric bronze Tin-plated  
Solder tads Phosphoric bronze Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-CB1.25-2AWT	1.25	7.65
HC-CB1.25-3AWT	2.50	8.90
HC-CB1.25-4AWT	3.75	10.15
HC-CB1.25-5AWT	5.00	11.40
HC-CB1.25-6AWT	6.25	12.65
HC-CB1.25-7AWT	7.50	13.90
HC-CB1.25-8AWT	8.75	15.15
HC-CB1.25-9AWT	10.00	16.40
HC-CB1.25-10AWT	11.25	17.65
HC-CB1.25-11AWT	12.50	18.90
HC-CB1.25-12AWT	13.75	20.15

**PCB LAYOUT**

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	HC-CB1.25-NAWT	版本 REV.	A						
			X.±0.25	X.*±2°		2013.07.01	品名 TITLE					1.25超薄贴片 WAFER SMT TYPE	页次 SHEET	1/1			
			.X±0.20	.X*±1°											2013.07.03	客户料号 CUTW. NO.	
			.XX±0.15	.XX*±0.5°													
.XXX±0.10	.XXX*±0.5°	单位 UNITS	MM	比例 SCALE	1:1												

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)  
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)  
[001000](#)