



SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

编 号	尺寸 (mm)		
	A	B	C
HC-HY-2Y	2.00	5.50	2.30
HC-HY-3Y	4.00	7.50	2.30
HC-HY-4Y	6.00	9.50	4.30
HC-HY-5Y	8.00	11.50	4.30
HC-HY-6Y	10.00	13.50	8.30
HC-HY-7Y	12.00	15.50	10.30
HC-HY-8Y	14.00	17.50	12.30
HC-HY-9Y	16.00	19.50	12.30
HC-HY-10Y	18.00	21.50	12.30
HC-HY-11Y	20.00	23.50	14.30
HC-HY-12Y	22.00	25.50	16.30
HC-HY-13Y	24.00	27.50	18.30
HC-HY-14Y	26.00	29.50	20.30
HC-HY-15Y	28.00	31.50	22.30
HC-HY-16Y	30.00	33.50	24.30

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENEAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	HC-HY-NY		版本 REV.	A				
			X.±0.25	X.*±2'		审核 CHECK	2013、07、01		品名 TITLE	HY孔座		页次 SHEET	1/1			
			.X±0.20	.X*±1'			核准 APPROVAL			张名			客户料号 CUTL. NO.			
			.XX±0.15	.XX*±0.5'						2013、07、03						
.XXX±0.10	.XXX*±0.5'	张名		深圳市华灿天禄电子有限公司 比例 SCALE 1:1												
单位 UNITS	MM	2013、07、05														

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#) [70-](#)
[4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-](#)
[001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#)
[819-22-004-30-001101](#)