



PCB LAYOUT

**SPECIFICATIONS**

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance:  $20\text{m}\Omega$  Max
- 5、Insulation Resistance:  $1000\text{M}\Omega$  Min
- 6、Withstanding Voltang:  $1000\text{V AC/minute}$
- 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-HY-2A	2.00	6.00
HC-HY-3A	4.00	8.00
HC-HY-4A	6.00	10.00
HC-HY-5A	8.00	12.00
HC-HY-6A	10.00	14.00
HC-HY-7A	12.00	16.00
HC-HY-8A	14.00	18.00
HC-HY-9A	16.00	20.00
HC-HY-10A	18.00	22.00
HC-HY-11A	20.00	24.00
HC-HY-12A	22.00	26.00
HC-HY-13A	24.00	28.00
HC-HY-14A	26.00	30.00
HC-HY-15A	28.00	32.00
HC-HY-16A	30.00	34.00

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生			料号 PART NO.	HC-HY-NA		版本 REV.	A					
			X.±0.25	X.'±2'		2013、07、01	张名	品名 TITLE		HY直针				页次 SHEET	1/1			
			.X±0.20	.X'±1'						2013、07、03	张名					客户料号 CUSTOM. NO.		
			.XX±0.15	.XX'±0.5'														
.XXX±0.10	.XXX'±0.5'	单位 UNITS	MM	比例 SCALE	1:1				深圳市华灿天禄电子有限公司									

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#)  
[61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-](#)  
[047](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#)  
[70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-](#)  
[T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)