


PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~ +85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer Nylon66 UL94-V0
PIN Brass Tin-plated

| Circuit | Part NO. | Dimensions mm | |
|---------|--------------|---------------|-------|
| | | A | B |
| 2 | HC-PH-2AW-X | 6.00 | 2.00 |
| 3 | HC-PH-3AW-X | 8.00 | 4.00 |
| 4 | HC-PH-4AW-X | 10.00 | 6.00 |
| 5 | HC-PH-5AW-X | 12.00 | 8.00 |
| 6 | HC-PH-6AW-X | 14.00 | 10.00 |
| 7 | HC-PH-7AW-X | 16.00 | 12.00 |
| 8 | HC-PH-8AW-X | 18.00 | 14.00 |
| 9 | HC-PH-9AW-X | 20.00 | 16.00 |
| 10 | HC-PH-10AW-X | 22.00 | 18.00 |
| 11 | HC-PH-11AW-X | 24.00 | 20.00 |
| 12 | HC-PH-12AW-X | 26.00 | 22.00 |
| 13 | HC-PH-13AW-X | 28.00 | 24.00 |
| 14 | HC-PH-14AW-X | 30.00 | 26.00 |
| 15 | HC-PH-15AW-X | 32.00 | 28.00 |
| 16 | HC-PH-16AW-X | 34.00 | 30.00 |

Ordering Information



| | | | | | | | | | | |
|-----------|--|--|------------------------|-------------------|-------------------|--|--|-------------|--------------|-----|
| | | | GENREL TOLERANCE | | 制 图 DRAWING | | 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD | | | |
| | | | DIM | TOL | 审 核 CHECK | | | | | |
| | | | X. X | ±0.30 | 批 准 APPROVAL | | 产品名称 TITLE | PH (2.0) 弯针 | 版本 REV. | A |
| 1 | | | X. XX | ±0.20 | 比 例 SCALE | | 产品料号 PART NO. | HC-PH-NAW-X | 单 位 UNITS | mm |
| 序号 No. | | | 变更内容 MODIFY CONTENT | 日期 MODIFY DATE | 投 影 Projection | | 材 料 MATERIAL | | 页 次 SHEET | 1/1 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [M90C108951C](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-024-10-](#)
[001000](#) [803-93-012-10-001000](#)