


- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperatuer Range: -25℃~ +85℃
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000mΩ Min
 - 6、Withstanding Voltang: 800V AC/minute
 - 7、Material: Wafer Nylon66 UL94-V0
PIN Brass Tin-plated

Circuit	Part NO.	Dimensions mm		
		A	B	C
2	HC-PHB-2x2AW	2.00	6.00	3.00
3	HC-PHB-2x3AW	4.00	8.00	3.00
4	HC-PHB-2x4AW	6.00	10.00	3.00
5	HC-PHB-2x5AW	8.00	12.00	5.00
6	HC-PHB-2x6AW	10.00	14.00	7.00
7	HC-PHB-2x7AW	12.00	16.00	9.00
8	HC-PHB-2x8AW	14.00	18.00	11.00
9	HC-PHB-2x9AW	16.00	20.00	13.00
10	HC-PHB-2x10AW	18.00	22.00	15.00
11	HC-PHB-2x11AW	20.00	24.00	17.00
12	HC-PHB-2x12AW	22.00	26.00	19.00
13	HC-PHB-2x13AW	24.00	28.00	21.00
14	HC-PHB-2x14AW	26.00	30.00	23.00
15	HC-PHB-2x15AW	28.00	32.00	25.00
16	HC-PHB-2x16AW	30.00	34.00	27.00
17	HC-PHB-2x17AW	32.00	36.00	29.00
18	HC-PHB-2x18AW	34.00	38.00	31.00
19	HC-PHB-2x19AW	36.00	40.00	33.00
20	HC-PHB-2x20AW	38.00	42.00	35.00

			GENERAL TOLERANCE		制 图 DRAWING		 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM	TOL	审 核 CHECK					
			X.X	±0.30	批 准 APPROVAL		产品名称 TITLE	PHB (2.0) 双排弯针	版本 REV.	A
			X.XX	±0.20	比 例 SCALE		产品料号 PART NO.	HC-PHB-2xNAW	单 位 UNITS	mm
			X.XXX	±0.10	投 影 Projection		材 料 MATERIAL		页 次 SHEET	1/1
			Angle	±3.0°						
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE								

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)