



2~5A

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material:Wafer Nylon46,UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-XA-2AW	2.50	7.50
HC-XA-3AW	5.00	10.00
HC-XA-4AW	7.50	12.50
HC-XA-5AW	10.00	15.00
HC-XA-6AW	12.50	17.50
HC-XA-7AW	15.00	20.00
HC-XA-8AW	17.50	22.50
HC-XA-9AW	20.00	25.00
HC-XA-10AW	22.50	27.50
HC-XA-11AW	25.00	30.00
HC-XA-12AW	27.50	32.50

PCB LAYOUT

GENERAL TOLERANCE		制 图 DRAWING 2013、07、01	料 号 PART NO. HC-XA-NAW	版 本 REV. A						
X.±0.25	X.*±2'				审 核 CHECK 张 名	品 名 TITLE XA-AW	页 次 SHEET 1/1			
.X±0.20	.X*±1'							核 准 APPROVAL 张 名	客 户 料 号 CUTM. NO.	
.XX±0.15	.XX*±0.5'									
.XXX±0.10	.XXX*±0.5'	深 圳 市 华 灿 天 禄 电 子 有 限 公 司								

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#)
[61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-](#)
[047](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#)
[70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-](#)
[T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)