





SPECIFICATION:

Current Rating: 3.0AMP

Contact Resistance: $20m \Omega (max)$

Insulation Resistance:1000M Ω Min at 500V DC Dielectric Strength:500V AC Per 1 Minute Operating Temperature: 40°C TO +105°C

MATERALS:

Insulator: P.B.T.+30% Glass Fibre(UL 94V-0)

Contact:Brass

Contact plated: 0.8u" Gold Over Nickel

Poles	Part No.	Dimension mm					
	raic no.	A	В	C			
10	310R-10P	31.90	10. 16	18. 60			
12	310R-12P	34. 44	12. 70	21. 14			
14	310R-14P	36. 98	15. 24	23. 68			
16	310R-16P	39. 52	17. 78	26. 22			
20	310R-20P	44. 60	22. 86	31. 30			
24	310R-24P	49. 68	27. 94	36. 38			
26	310R-26P	52. 22	30. 48	38. 92			
30	310R-30P	57. 30	35. 56	44. 00			
34	310R-34P	62. 38	40. 64	49. 08			
40	310R-40P	70. 10	48. 26	56. 70			
50	310R-50P	82. 70	60. 96	69. 40			
60	310R-60P	95. 40	73.66	82. 10			
64	310R-64P	100. 48	78. 74	87. 18			

		APPROVED:	DATE:	深圳市华灿天禄电子有限公司								
		CHECKED:	DATE:	TITLE:								
TOLERANCE TABLE				NJ-2. 54-2*NPW								
.0	\pm 0.30			CLIENT	P/N		/					
. 00	±0.20	DRAWN:	DATE:	UNIT	mn	n ´	SCALE	free		-		1
				FILE NO.		•	OCILL	11.00		Ψ	\geq	1
. 000	±0.05	LYF	2008-04-07			Ckmtw-310-00003				REV.	1	١.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by HCTL manufacturer:

Other Similar products are found below:

571763P 61-168618-12P D20419-211 72.250.1628.2 72.250.2428.2 76.350.0729.0 76871-1403 PCR-E36PM PCS-XE26LKA PCS-XES68MS+ G38A71314B 9776-18-6 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 91-644626-35P 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G730VID08BDC24 HDMR-29-01-S-SM-TR HDRA-E68W1LFDTC-SL+ 54182-0605 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 10-565995-597N 10-584459-12P 5554841-1 SM3106F14S-7S-LC SM3106R18-18S U90B3054061110 U65-E04-4020 ZPF00000000000097891 557-262M2-06C PCS-96LFD+ 60-042222-02S 10099439-003C-TRLF