


PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~ +85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer Nylon66 UL94-V0  
PIN Brass Tin-plated

| Circuit | Part NO.     | Dimensions mm |       |
|---------|--------------|---------------|-------|
|         |              | A             | B     |
| 2       | HC-PH-2AW-X  | 6.00          | 2.00  |
| 3       | HC-PH-3AW-X  | 8.00          | 4.00  |
| 4       | HC-PH-4AW-X  | 10.00         | 6.00  |
| 5       | HC-PH-5AW-X  | 12.00         | 8.00  |
| 6       | HC-PH-6AW-X  | 14.00         | 10.00 |
| 7       | HC-PH-7AW-X  | 16.00         | 12.00 |
| 8       | HC-PH-8AW-X  | 18.00         | 14.00 |
| 9       | HC-PH-9AW-X  | 20.00         | 16.00 |
| 10      | HC-PH-10AW-X | 22.00         | 18.00 |
| 11      | HC-PH-11AW-X | 24.00         | 20.00 |
| 12      | HC-PH-12AW-X | 26.00         | 22.00 |
| 13      | HC-PH-13AW-X | 28.00         | 24.00 |
| 14      | HC-PH-14AW-X | 30.00         | 26.00 |
| 15      | HC-PH-15AW-X | 32.00         | 28.00 |
| 16      | HC-PH-16AW-X | 34.00         | 30.00 |

Ordering Information



|           |                        |                   | GENEAL TOLERANCE | 制 图<br>DRAWING    | 深圳市华灿天禄电子有限公司<br>ShenzhenhuacantianluELECTRONICS CO.,LTD |             |              |     |  |
|-----------|------------------------|-------------------|------------------|-------------------|--|-------------|--------------|-----|--|
|           |                        |                   | DIM TOL          | 审 核<br>CHECK      |  |             |              |     |  |
|           |                        |                   | X. X ±0.30       | 批 准<br>APPROVAL   | 产品名称<br>TITLE  | PH (2.0) 弯针 | 版本<br>REV.   | A   |  |
| 1         | 初版发行                   |                   | X. XX ±0.20      | 比 例<br>SCALE      | 产品料号<br>PART NO.   | HC-PH-NAW-X | 单 位<br>UNITS | mm  |  |
| 序号<br>No. | 变更内容<br>MODIFY CONTENT | 日期<br>MODIFY DATE | X. XXX ±0.10     | 投 影<br>Projection | 材 料<br>MATERIAL  |             | 页 次<br>SHEET | 1/1 |  |
|           |                        |                   | Angle ±3.0°      |                   |  |             |              |     |  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)