





SPECIFICATIONS
 Current Rating:3.0AMP
 Contact Resistance:10mΩMax
 Dielectric Strength:Min 1000V RMS
 Operation Temperature:-40°C to +105°C

Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)

Contact Material:Brass
 Contact Clip(4/6 finger):Becu(C17200)
 Accepted Pin:∅0.40 to 0.60mm
 Insulator Material:Polyester(UL94V-0)
 Standard: PPS
 Soldering temperature: 260°C±5° 5S



Ordering Information

PM 200 - * - N - Z - * - ** - C

No.of Rows 1=Single Row 2=Dual Row	No.of Pins 2-40Pin	Type Z=0° Z=90°	Length (mm)	Contact G0:Gold G1:1u" Gold G2:5u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin	Plating	Round Pin (mm)
--	-----------------------	-----------------------	----------------	--	---------	-------------------

			GENREL TOLERANCE		制图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM	TOL	审核 CHECK					
			X.X	±0.30	批准 APPROVAL		产品名称 TITLE	2.0 双排 排母 圆直针	版本 REV.	A
1			初版发行				产品料号 PART NO.	PM200-2-N-Z-3.0-XX-C	单位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°	投影 Projection		材料 MATERIAL		页次 SHEET	1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)