


Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

SPECIFICATIONS

Current Rating:2.0AMP
 Contact Resistance:20mΩ Max
 Dielectric Strength:Min 1000V RMS
 Operation Temperature:-40°c to +105°c
 Contact Material:Brass
 Contact Plating:Au Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PPS
 Soldering Temperature: 260°C±5° 5S



Ordering Information

PZ 200 - * - N - Z - ** - C

No. of Rows
1=Single Row
2=Dual Row

No. of Pins
2-40Pin

Type
Z=直排针
N=弯排针
R=圆插

Contact Plating
C0:Gold Flash
C1:1u" Gold
C2:3u" Gold
C3:5u" Gold
C4:10u" Gold
C5:15u" Gold
C6:30u" Gold
S0:Gold Flash/Tin
S1:Tin

Round Pin
(圆针)

| | | | | | | | | | | | |
|-----------|------------------------|-------------------|-------------------|-------|-------------------|--|--|--|-----------------------------------|--------------|-----|
| | | | GENERAL TOLERANCE | | 制 图 DRAWING | | 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD | | | | |
| | | | DIM | TOL | 审 核 CHECK | | 产品名称 TITLE | | 2.0 双排 直排针 塑高3.0 (上针0.5 下针0.5) | 版本 REV. | A |
| | | | X.X | ±0.30 | 批 准 APPROVAL | | 产品料号 PART NO. | | PZ200-2-N-Z-XX-C | 单 位 UNITS | mm |
| | | | X.XXX | ±0.10 | 比 例 SCALE | | 材 料 | | | 页 次 SHEET | 1/1 |
| 序号 No. | 变更内容 MODIFY CONTENT | 日期 MODIFY DATE | Angle | ±3.0° | 投 影 Projection | | | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)