



Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ±0.05)

SPECIFICATIONS

Current Rating: 2.0AMP
 Contact Resistance: 20mΩ Max
 Dielectric Strength: Min 1000V RMS
 Operation Temperature: -40°C to +105°C

Contact Material: Brass
 Contact Plating: Au Over Ni
 Insulator Material: Polyester (UL94V-0)
 Standard: PPS
 Soldering Temperature: 260°C ± 5° 5S

Ordering Information

PZ 200 - * - N - Z - ** - C

- No. of Rows
1=Single Row
2=Dual Row
- No. of Pins
2-40 Pin
- Type
Z=直排
N=弯排
R=圆插
- Contact Plating
C0: Gold Flash
C1: 1u" Gold
C2: 3u" Gold
C3: 5u" Gold
C4: 10u" Gold
C5: 15u" Gold
C6: 30u" Gold
S0: Gold Flash/Tin
S1: Tin
- Round Pin (圆针)

			GENERAL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD				
			DIM	TOL	审 核 CHECK		产品名称 TITLE		2.0 双排 直排针 塑高3.0 (上针0.5 下针0.5)	版本 REV.	A
			X. X	±0.30	批 准 APPROVAL		产品料号 PART NO.		PZ200-2-N-Z-XX-C	单 位 UNITS	mm
1			初版发行		X. XX		比例 SCALE			页 次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X. XXX		Angle		投 影 Projection			材 料 MATERIAL	
			±0.10		±3.0°						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)