



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

SPECIFICATIONS
 Rated Current: 3.0AMP
 Contact Resistance: 20m Ω Max
 Withstand Voltage: 1000V AC/DC
 Insulation Resistance: 1000M Ω Min
 Operation Temperature: -40 $^{\circ}$ c to +105 $^{\circ}$ c

Contact Material: Brass
 Contact Plating: Au Or Tin Over Ni
 Insulator Material: Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 230 $^{\circ}$ C for 30-60 seconds
 (260 $^{\circ}$ C for 10 seconds)

Dimension antitheses list			
ITEM	PA	PB	PC
Standard	6.00	4.40	3.00
Alternate			

Ordering Information

PZ 254 - * - N - W - 8.5 - **

No.of Rows 1=Single Row 2=Dual Row	No.of Pins 2-40Pin	Type 2-直针 8-弯针 8S-弯插	Contact Plating G0:Gold Flash G1:1 μ " Gold G2:3 μ " Gold G3:5 μ " Gold G4:10 μ " Gold G5:15 μ " Gold G6:30 μ " Gold S0:Gold Flash/Tin S1:Tin
--	-----------------------	-------------------------------	--

			GENREL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD				
			DIM	TOL	审 核 CHECK		产品名称 TITLE		2.54单排 正弯排针(塑高2.5)	版本 REV.	A
			X.X	± 0.30	批 准 APPROVAL		产品料号 PART NO.		PZ254-1-N-W-8.5-XX	单 位 UNITS	mm
1			X.XX	± 0.20	比 例 SCALE		材 料			页 次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X.XXX	± 0.10	投 影 Projection		材 料 MATERIAL				
			Angle	$\pm 3.0^{\circ}$							

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HCTL](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)