


PANEL CUT-OUT		X
Z	Y	X
0.70~1.25	9.00~9.10	13.50~13.60
1.25~2.00	9.00~9.10	13.60~13.70

NOTES:

1. Rating:  
VDE ENEC 3A 250VAC T125/55  
UL cUL 6GPA 125VAC/3GPA 250VAC T105/55  
CCC 3A 250VAC, 3A/40A 250VAC T105/55
2. Circuit Diagram: 3P ON-ON
3. Terminal Strength: ≥40N
4. Electrical life: ≥10000 cycles
5. Withstand Voltage: Withstand Voltage: 1500VAC 1min  
Terminals to Button: 3000VAC 1min  
Leakage Current: 1mA
6. Current resistance: ≤50mΩ (initial)
7. Insulation resistance: ≥100MΩ
8. Body Material: NYLON 66 94V-0~2



普通公差:  
COMMON TOLERANCE:

A4			
A3			
A2		UP TO 5	±0.20
A1		ABOVE 5 TO 30	±0.30
REV.	DATE	REVISION DESCRIPTION	ISSUE
			ANGULAR ±5°

单位	mm	投影	梁金勇	产品名称	跷板开关	比例	Free
绘图	周金勇	核校	周培雷	型号	RS601H		
日期	2015.09.19	批准		图号	RS601HL-1020011BB		

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Rocker Switches](#) category:*

*Click to view products by [HCTL](#) manufacturer:*

Other Similar products are found below :

[LTILA6E-1S-WH-RC-FN12VXCR1](#) [6-1571986-9](#) [8055K23Z7V](#) [8055K52Z7V](#) [8138K20E6M50](#) [PREDD5-07F-BB0GW](#) [999-16716-002](#)  
[999-16716-003](#) [999-16716-004](#) [A101J1V3Q004](#) [A101J2ZQ004](#) [A101J51CB0004](#) [A103J1ZQ004](#) [A201J1AQ004](#) [A201J50ZQ004](#)  
[A203J51ZQ0004](#) [A435S1YZQ](#) [H8653VBBG2577W](#) [HB130CHNWWNAAC](#) [R13112ABB-602W](#) [1251.0303](#) [1352.0107](#) [1363.0201](#)  
[AML25GBF2AA03GR](#) [1500G51E](#) [1571099-3](#) [1571987-4](#) [1571987-5](#) [1571988-5](#) [B123J77V7B2](#) [B226J50W4Q22P](#) [B433J37ZQ22M](#)  
[160212E](#) [1634200-7](#) [1801.1164](#) [1839.1502](#) [PANEL-PLUG-VHP-BLACK](#) [PANEL-PLUG-VHP-WT](#) [K1ABBSCADN](#) [K2ABAAAAAA](#)  
[KG312A2DXD246X](#) [250011E714](#) [2600R21E](#) [260413E](#) [2639LH/2A7/127000L0](#) [LL3AZXX-100-XGT1](#) [LL3AZXX-100-XHS1](#) [LL3AZXX-](#)  
[100-XSD1](#) [30-695B](#) [160311E](#)