

High Definition VideoScope Inspection Cameras

Narrow diameter cameras with 5.7" High Definition Color LCD* Monitor Deliver high image resolution on large color display where images and videos can be stored on SD memory card (included)

Features:

- Model HDV610 5.5mm diameter camera head with 1m flexible cable Model HDV620 - 5.8mm diameter camera head with 1m semi-rigid cable
- 5.7" color LCD* TFT with high definition 640 x 480 VGA pixel resolution
- Mini, high-resolution water-proof (IP57) camera head
- Rugged oil/chemical resistant and water/drop proof housing (IP67/2m)
- Non-slip ergonomic handles for ambidextrous use
- SD memory card included to store >15,000 images
- Video recording (up to 4 hours) with Voice annotation
- AV output for viewing images and video directly on a monitor
- Video and images can be transferred to a PC via the SD card or USB output
- An optional wireless transmitter (HDV-WTX) connects to your camera cable and allows you to transmit video up to 100ft (30m) from the measurement point to your monitor







- A. Camera with 4 built-in bright LED I illuminate dark areas.
- B. HDV-WTX Optional Wireless Tra transmits video to the main display tight or hard to reach places up to (30m) away
- C. Optional Articulating (6mm diamet camera probes adjust up to 240° viewing angle (see below for ordering)

| | Carried Manager | NOVOS INC |
|-----------------|------------------------|---|
| | Specifications | |
| | Camera | |
| | Minimum Focus distance | 2.36" (60mm); macro: 0.59" (15mm) |
| | Field of View | 65° |
| | Shaft diameter | HDV610: 0.22" (5.5mm) |
| lights | | HDV620: 0.23" (5.8mm) |
| | Working length | 39" (1m) |
| ansmitter | Borescope | |
| y from 100ft | *LCD Color TFT Display | 5.7" (14.5cm) size; 5.3" (13.5cm) viewable |
| | Pixels | 640 x 480 VGA pixel resolution |
| ter) viewina | I IAGIG | (320 x 240 for 4mm camera) |
| viewing | | |

Ordering Information:

HDV610High Definition VideoScope (5.5mm diameter/1m Flexible Cable) HDV620High Definition VideoScope (5.8mm diameter/1m Semi-Rigid Cable)

Video Inspector Monitor (order camera head separately from accessories listed below) HDV600High Definition VideoScope (Monitor and hard carrying case only)

| Optional camera accessories |
|---|
| HDV-TX16mm Articulating VideoScope Camera Head with Macro lens and 1m Semi-Rigid Cable |
| HDV-WTX16mm Wireless Articulating VideoScope Camera Head w/Macro lens & 1m Semi-Rigid Cable |
| HDV-TX26mm Articulating VideoScope Camera Head w/Macro lens and 2m Semi-Rigid Cable |
| HDV-WTX2 |
| HDV-4CAM-1FM4mm VideoScope Camera Head with Macro lens and 1m Flexible Cable |
| HDV-4CAM-5FM4mm VideoScope Camera Head with Macro lens and 5m Flexible Cable |
| HDV-5CAM-1FM5.5mm VideoScope Camera Head with Macro lens and 1m Flexible Cable |
| HDV-5CAM-3F5.5mm VideoScope Camera Head with long depth of field and 3m Flexible Cable |
| HDV-5CAM-3FM5.5mm VideoScope Camera Head with Macro lens and 3m Flexible Cable |
| HDV-5CAM-30FM5.5mm VideoScope Camera Head with Macro lens and 30m Flexible Cable |
| HDV-5CAM-10F5.5mm VideoScope Camera Head with long depth of field and 10m Flexible Cable |
| HDV-5CAM-1R5.8mm VideoScope Camera Head with long depth of field and 1m Semi-Rigid Cable |
| HDV-5CAM-1RM5.8mm VideoScope Camera Head with Macro lens and 1m Semi-Rigid Cable |
| HDV-5CAM-3R5.8mm VideoScope Camera Head with long depth of field & 3m Semi-Rigid Cable |
| HDV-5CAM-3RM5.8mm VideoScope Camera Head with Macro lens and 3m Semi-Rigid Cable |
| HDV-25CAM-10G25mm VideoScope Camera Head with long depth of field and 10m Fiberglass Cable |
| HDV-25CAM-30G25mm VideoScope Camera Head with long depth of field and 30m Fiberglass Cable |
| HDV-WTXWireless Transmitter |
| HDV-PCSpare Patch Cable for HDV Series |
| ADPTR-HDVReplacement AC Adaptor |

HDV610 and HDV620 Include:

· VideoScope, SD memory card, handset with camera probe and 1m cable (Probe accessories: magnet, 45° mirror, and anti-snag tip), 3.7V rechargable Li-Polymer battery, patch cable, Universal AC adapter (110-240V, four plugs), USB and AV cables, and hard carrying case

Applications:

- Industrial Processing & Manufacturing
- · Heavy Equipment
- HVAC/Boilers
- Aerospace

Frame Rate

SD Card

Operating

- · Government & Security
- Insurance
- · Mining and Aggregate
- · Aviation AOG and FBO
- Power Generation

30 fps frame rate (NTSC & PAL)

2GB SD memory card included (supports up to 32GB SD storage)

up to 4 hours AVI video

- Building Inspection & Commissioning
- · PetroChem/Refineries
- Infrastructure



Camera probes with cable length greater than 3m will be coiled on a spool as shown on the left.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160