

## Specification Sheet

Part Number: 109-00001



Q Tie, 4.1" Long, 18lb Tensile Strength, PA66, Natural, 100/pkg

**Article Number**

109-00001

**Type**

Q18R

**Color**

Natural (NA)

**Features & Benefits**

- Open-head design with easily detectable slot opening allows for swift and easy insertion
- Pre-lock feature allows for a temporary hold
- The large ribbed tail permits an ergonomic installation
- Two rails on the strap ensure guidance through the cable tie head

**Quantity Per**

bag

<b>Product Description</b>	Q-Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head provides ease of placement when working with gloves or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q-Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.
<b>Short Description</b>	Q Tie, 4.1" Long, 18lb Tensile Strength, PA66, Natural, 100/pkg
<b>Global Part Name</b>	Q18R-PA66-NA
<b>Minimum Tensile Strength (Imperial)</b>	18.0
<b>Minimum Tensile Strength (Metric)</b>	80
<b>Length L (Imperial)</b>	4.1
<b>Length L (Metric)</b>	105
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.1
<b>Width W (Metric)</b>	2.6

<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	2.0
<b>Bundle Diameter Max (Imperial)</b>	0.9
<b>Bundle Diameter Max (Metric)</b>	24.0
<b>Thickness T (Imperial)</b>	0.039
<b>Thickness T (Metric)</b>	1.0
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   ANSI/UL 62275 UL   ANSI/UL 746B UL   ANSI/UL 1565
<b>UL Listed (US and Canada)</b>	Yes

<b>UL Listed (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Hellermann](#) manufacturer:*

Other Similar products are found below :

[T18RPOCKETPAC](#) [380-03003](#) [406064A](#) [TSR1I-21](#) [TSR1I-29](#) [TSR1I-33](#) [TSR1I-36](#) [105-4JW8](#) [MS3109-12AU](#) [Q30LR-PA66-BK-C1](#) [Q18I-PA66-NA-C1](#) [Q18R-PA66-NA-C1](#) [CTQM5-PA66-BK-C1](#) [308-10600](#) [T50IDH0C2](#) [AS25](#) [T18MR-NAT\(100 PACK\)](#) [T120L.NN2P](#) [MK7.9A](#) [181-50840](#) [621-10405](#) [164-21008](#) [TWT2](#) [G51P-A-PE-NA](#) [E4500](#) [GT.50X66P2](#) [TSRI-JB2](#) [111-01626](#) [SBS4 NATURAL](#) [SBPEFR4-PE-BK-30M](#) [308-30421](#) [309-65129](#) [309-65213](#) [309-65298](#) [309-65164](#) [HIS-3-9/3-PEX-BU](#) [HIS-3 6/2 BRN](#) [HGDC1-3CC/7](#) [HEGPA6612 GREY](#) [T50RS5.NB3P](#) [T150M-NAT](#) [HGDC1-3BW/3](#) [HG1-3](#) [HIS-3 3/1 BLU](#) [HGDC2-5BW/N](#) [HGDC2-5BW/L](#) [TSR1I-25](#) [RSB3](#) [RT250XL9X2](#) [SLHD3X2G4](#)