

## Specification Sheet

Part Number: 111-01125



High-Temp Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, ETFE, Blue, 50/pkg

**Article Number** 111-01125

**Type** T120R

**Color** Blue (BU)

**Features & Benefits**

- ETFE cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.
- Inside serrations allows for strong grip on cables and wire bundles.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

<b>Product Description</b>	ETFE ties provide excellent protection against radiation, ultraviolet light, and a wide range of chemicals. They are also rated for low outgassing applications. HellermannTyton's ETFE ties come in a standard color of blue for easy identification. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	High-Temp Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, ETFE, Blue, 50/pkg
<b>Global Part Name</b>	T120R-E/TFE-BU
<b>Minimum Tensile Strength (Imperial)</b>	120.0
<b>Minimum Tensile Strength (Metric)</b>	535.0
<b>Length L (Imperial)</b>	15.2
<b>Length L (Metric)</b>	387.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.29
<b>Width W (Metric)</b>	7.4

<b>Bundle Diameter Min (Imperial)</b>	0.59
<b>Bundle Diameter Min (Metric)</b>	15.0
<b>Bundle Diameter Max (Imperial)</b>	4.13
<b>Bundle Diameter Max (Metric)</b>	105.0
<b>Thickness T (Imperial)</b>	0.075
<b>Thickness T (Metric)</b>	1.9
<b>Material</b>	Ethylentetrafluoroethylene (E/TFE)
<b>Material Shortcut</b>	E/TFE
<b>Flammability</b>	UL 94 V0
<b>Operating Temperature (Metric)</b>	-112°F to +338°F (-80°C to +170°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   ANSI/UL 1565 UL   ANSI/UL 746B UL   ANSI/UL 62275
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes

<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	5.2

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)