

157-00107

Article Number: 157-00107

Description: 1-Piece Cable Tie/Fir Tree Mount With Disc, 6.3"L, 6.3-7 mm Mounting Hole, PA66HIRHSUV, Bk, 1000/pkg



Base Data	Local Order Number	157-00107	
	Type	T50SOSFT6LG-E	
	Color	Black (BK)	
	Features and benefits	<ul style="list-style-type: none"> • One piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables. • The design of the fir tree ensures a positive and secure fixing into panels with thicknesses from 0.8mm to 7.0mm or threaded blind holes. • Disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. 	
	Quantity Per	bag	
	Product Description	Fir Tree Mounts offers a simple and easy to use method of bundling and mounting cables. The design of the fir tree ensures a secure and robust fit into panels with a round mounting hole between thicknesses between .03" - .28". The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. The outside serrated tie can be applied by hand and tensioned with one of HellermannTyton's manual or pneumatic hand tools.	
	Global Part Name	T50SOSFT6LG-E-PA66HIRHSUV-BK	
	Short Description	1-Piece Cable Tie/Fir Tree Mount With Disc, 6.3"L, 6.3-7 mm Mounting Hole, PA66HIRHSUV, Bk, 1000/pkg	
	Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
		Minimum Tensile Strength (Metric)	180N
Length L (Imperial)		6.3"	
Length L (Metric)		165.0mm	
Fixation Method		Fir Tree	
Identification Plate Position		none	
Releasable Closure		No	
Tie Closure		plastic pawl	
Variant		Outside Serrated	
Width W (Imperial)		0.18"	
Width W (Metric)		4.6mm	

157-00107



Product Dimensions	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.28"
	Panel Thickness Max. (Metric)	7.00mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.70mm
	Mounting Hole Diameter D (Imperial)	0.25 - 0.28"
	Mounting Hole Diameter D (Metric)	6.3 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.248"
	Mounting Hole Diameter D Max. (Imperial)	0.275"
	Thickness T (Imperial)	0.05"
Thickness T (Metric)	1.3mm	
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987
	Weight (Metric)	1.50kg

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIN 41612 Connectors](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[09231126901](#) [PCN10F-24P-2.54DS\(72\)](#) [004.767](#) [02221602702](#) [024069](#) [602427301412000](#) [013275](#) [691327-1](#) [74670-0732](#) [74680-0340](#)
[75880-0015](#) [76453-0014](#) [86093159ALF](#) [923454](#) [QLC260R](#) [120X10099X](#) [120X10019X](#) [120X10089X](#) [120X10129X](#) [121A10039X](#)
[121A10309X](#) [122A10019X](#) [122A10029X](#) [122A10249X](#) [122A10669X](#) [122A11089X](#) [122A13089X](#) [121B10409X](#) [122A10089X](#)
[122A10129X](#) [122A10349X](#) [122A13359X](#) [1377391-4](#) [DIN-048CPC-SR1-MH](#) [1393583-2](#) [1393726-7](#) [140X10059X](#) [140X10129X](#) [143-1913-](#)
[000](#) [143-1908-000](#) [1484472-1](#) [173052](#) [2110070-1](#) [2110070-2](#) [CBC20T00-008FDS5-0-1-002VR](#) [983-0SE12-12P6](#) [17041102202](#) [172699-](#)
[5036](#) [173051](#) [20 8457096 010 025](#)