

## Specification Sheet

Part Number: 2P9C



Spiralwrap Protective Sheathing, 0.25" Diameter, PTFE, Natural, 100 ft/roll

**Article Number** 161-05047

**Type** 2P

**Color** Natural (NA)

**Features & Benefits**

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

**Quantity Per** reel

**Product Description** HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

<b>Short Description</b>	Spiralwrap Protective Sheathing, 0.25" Diameter, PTFE, Natural, 100 ft/roll
<b>Global Part Name</b>	2P-PTFE-NA
<b>Length L (Imperial)</b>	100.0
<b>Length L (Metric)</b>	30.48
<b>Variant</b>	Spiral Binding
<b>Bundle Diameter Min (Imperial)</b>	0.18
<b>Bundle Diameter Min (Metric)</b>	4.75
<b>Bundle Diameter Max (Imperial)</b>	2.0
<b>Bundle Diameter Max (Metric)</b>	50.8
<b>Diameter D (imperial)</b>	0.25
<b>Diameter D (metric)</b>	6.35
<b>Nominal Diameter (Imperial)</b>	0.25
<b>Nominal Diameter (Metric)</b>	6.35
<b>Wall Thickness WT (Imperial)</b>	.030
<b>Wall Thickness WT (Metric)</b>	0.76

<b>Material</b>	Polytetrafluoroethylene (PTFE)
<b>Material Shortcut</b>	PTFE
<b>Flammability</b>	Non-Flammable
<b>Halogen free</b>	No
<b>Operating Temperature (Metric)</b>	-449°F to +500°F (-267°C to +260°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.48
<b>Customs Number</b>	3926909988

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[6984850001](#) [8426-11](#) [5026790001](#) [5026800002](#) [5026810001](#) [5026820001](#) [502679N003](#) [RAY-101-3.0\(100\)](#) [100-001A250](#) [1200068](#) [RBK-ESS-CROSS-10.0-X-8MM](#) [AA59569R34T0781](#) [100-003A078](#) [561-W48BK/C](#) [CQ50393001](#) [CQ50453001](#) [102-051-016](#) [167-00217](#) [CS-A900T](#) [THP6B](#) [106815-0381](#) [5418A-500-CU](#) [7644-T-110](#) [8424-8](#) [8425-8](#) [4545](#) [AF1554-NA005](#) [G1101/4-BK005](#) [G1201/8-BK002](#) [P1050-BK005](#) [P10517-CL005](#) [P10522-BK005](#) [PF13012-BK002](#) [PF1307/8-BK005](#) [PF20016-NA005](#) [PF2003-NA005](#) [PF2007/16-NA005](#) [PF2008-NA005](#) [PIF-200-1/2A-NA008](#) [SW21-NA002](#) [SW14-WH005](#) [TFT20011-NA002](#) [TFT2009-NA002](#) [TFT25024-NA001](#) [XS200N1/4-BK002](#)  
[1200135](#) [1200194](#) [1205137](#) [CCF-1 1/2-8-12](#) [SC-3/4](#)