



Manual Tensioning Tool with Plastic Housing

- EVO7 up to 4.8 mm strap width

Features and Benefits

- Ergonomic, slip-proof handle for a comfortable and secure grip
- Extremely low maintenance
- Fast and precise application with minimum effort (TLC mechanism)
- Convenient and simple tension adjustment
- Extended, slim nose for use in narrow spaces
- Housing made of resilient and lightweight glass fibre-reinforced polyester
- Standard grip span (90 mm) and short grip span (80 mm) available



EVO7.

TYPE	Strap Width max. (G)	Strap Thickness max.	Weight	Article-No.
EVO7	4.8	1.5	0.275 kg	110-70129
EVO7SP	4.8	1.5	0.275 kg	110-70130
BLADEKIT	-	-	-	110-70106

All dimensions in mm. Subject to technical changes.

TLC-Technology: Tension - Lock - Cut

The new EVO7 protects muscles and joints and increases effectiveness

- Less recoil shock reduces impact to the operator's hand
- Application of force is significantly reduced



One Step to the Web!



1: Tension: Tie is tensioned as usual.

2: Lock: When the desired tension is met the locking mechanism locks the tie in place.



3: Cut: Innovative, effortless and less recoil shock cut-off function.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hellermann](#) manufacturer:

Other Similar products are found below :

[111-03250](#) [RSB2](#) [T18RPOCKETPAC](#) [380-03003](#) [406064A](#) [TSR1I-21](#) [TSR1I-29](#) [TSR1I-33](#) [TSR1I-36](#) [1122-4JW8](#) [1126-4JW8](#) [RSB6](#)
[MS3109-12AU](#) [Q30LR-PA66-BK-C1](#) [Q18I-PA66-BK-C1](#) [CTQM5-PA66-BK-C1](#) [LKCSF1.NB3P](#) [HWCLIP16 BLACK](#) [T50IDH0C2](#)
[LOK01B.NB3P](#) [AS45](#) [T120R.RN3P](#) [184-10168](#) [MK7.9A](#) [181-50840](#) [TWT2](#) [MCTPP120R](#) [MBT14SFC](#) [E4500](#) [TSRI-JB2](#) [309-65110](#) [309-](#)
[65129](#) [309-65214](#) [309-65298](#) [309-65300](#) [309-65117](#) [309-65118](#) [309-65164](#) [NGM20-RED](#) [NGM32-DGY](#) [GSS3](#) [321-50012](#) [H75X25](#)
[BLACK 500](#) [HIS-3-9/3-PEX-CL](#) [HIS-3 12/4 CLR](#) [HISA-18/6-PEX-CL](#) [HGDC2-5BW/1](#) [HELADUCT FLEX30 SK](#) [T50RS5.NB3P](#) [T30LR](#)