# **HellermannTyton**

# **Product Safety Data Sheet**

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION & COMPANY/UNDERTAKING

# PRODUCT NAME:

# Helagrip and Ovalgrip Markers

Address/Phone No:

Hellermann Tyton International Medical and Technology Park William Prance Road Plymouth Devon PL2 3NX (01752) 701261

# 2. HAZARDOUS IDENTIFICATION

Under normal conditions of use, harmful effects are unlikely.

# 3. COMPOSITION/INFORMATION OF INGREDIENTS

PRODUCT DESCRIPTION: Flexible PVC tubing and cable markers

HAZARDOUS INGREDIENT(S)	CAS No.	%(w/w)	Symbol	R Phrases
Antimony Trioxide	1309-64-4	<10%	Xn	R40

#### 4. FIRST-AID MEASURES

Inhalation:	If burning, remove from source of noxious fumes. Administer artificial respiration or oxygen if necessary. Seek medical attention.
Skin Contact:	Drench the skin with plenty of cold water and cover with a clean dressing. Do not attempt to remove molten material. Have any burns treated by a physician.
Eye Contact: Ingestion:	Irrigate thoroughly with water for at least 10 minutes. Obtain medical attention. Do not ingest. If ingested, seek medical help.

#### 5. FIRE-FIGHTING MEASURES

Extinguishing Media:	Dry powder, water mist, foam.
Fire Fighting Protective Equipment:	In a fire situation, toxic and corrosive vapours will be evolved and self-contained breathing apparatus should be worn.

### PRODUCT NAME:

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Not anticipated

Spill Response: Not applicable

Methods for Disposal: Dispose of waste product in a sanitary landfill.

#### 7. HANDLING & STORAGE

### 1.1 HANDLING

#### **Process Hazards**

Avoid handling product when being recovered with heat gun or flame torch. Do not touch until allowed to cool. Recover product in well-ventilated areas.

#### 1.2 STORAGE

Store away from heat and direct sunlight, store below 40°C.

Shelf Life: 5 years under above conditions

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Occupational Exposure Limits**

None associated.

- Eye Protection: Avoid eye contact with vapours or smoke resulting from over-heating or when used in confined areas.
- Hand Protection: Avoid skin contact with hot material. Wear appropriate gloves to prevent thermal burns.

Ingestion: Wash hands after handling, and before eating.

Recommended Ventilation: Local exhaust is required for operations using large amounts of material. Conduct air monitoring to determine adequacy of ventilation. Use in a well-ventilated area. When using this product in a confined space or where ventilation may be inadequate, then respiratory protection may be worn. Inadequate ventilation or confined spaced would cause vapours from heating of this product to be present in the user's breathing zone and may cause respiratory irritation. Excessive heating of this product may result in thermal degradation and decomposition products, which may result in adverse health effects.

# 9. PHYSICAL & CHEMICAL PROPERTIES

Form	:	Extruded beading, tubing and markers
Colour	:	Various
Odour	:	Odourless
Odour Threshold (ppm)	:	N/A
pH (Value)	:	N/A
Boiling Point (°C)	:	N/A
Density (g/ml)	:	1.0 nominal
Solubility (Water)	:	Not soluble

#### 10. STABILITY & REACTIVITY

Hazardous Reactions	:	Stable unless overheated or combusted.
Hazardous Decomposition Produc	t(s) :	Hydrogen Chloride, Carbon Monoxide.

#### 11. TOXICOLOGICAL INFORMATION

Inhalation	:	Not applicable at normal working temperatures.
Skin Contact	:	No effects at room temperature observed.
Eye Contact	:	Eye contact is not a likely route of exposure to this product.
Ingestion	:	Ingestion is not a likely route of exposure to this product.
Long Term Exposure	:	None observed.

# **12. ECOLOGICAL INFORMATION**

PVC products are considered to be ecologically benign. They are not readily decomposed by weathering or micro-organisms.

### **13. DISPOSAL CONSIDERATIONS**

In accordance with National and Local Regulations

Can be incinerated in a commercial incinerator.

PRODUCT NAME:

#### 14. TRANSPORT INFORMATION

No special requirements. Not a hazardous good as defined within international regulations.

#### **15. REGULATORY INFORMATION**

Not defined as hazardous as per 67/548/EEC and 1999/45/EC. Product is compliant with EU Directives 2002/95/EC (RoHS) 2002/96/EC (WEEE) 2003/11/EC (pentabromodiphenyl ether, octabromodiphenyl ether) 2006/122/EC (PFOS)

#### **16. OTHER INFORMATION**

This data sheet was prepared in accordance with Regulation (EC) No 1907/2006 (REACH)

Use: Insulation, protection and cable identification.

For other technical information, contact the address in Section 1.

Information in this publication is believed to be accurate and is given in good faith, but it is for the Customer to satisfy itself of the suitability for its own particular purpose. Accordingly, HellermannTyton gives no warranty to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hellermann manufacturer:

Other Similar products are found below :

 111-03250
 RSB2
 T18RPOCKETPAC
 380-03003
 406064A
 TSR1I-21
 TSR1I-33
 TSR1I-36
 1122-4JW8
 1126-4JW8
 RSB6

 MS3109-12AU
 Q30LR-PA66-BK-C1
 Q18I-PA66-BK-C1
 CTQM5-PA66-BK-C1
 LKCSF1.NB3P
 HWCLIP16
 BLACK
 T50IDH0C2

 LOK01B.NB3P
 AS45
 T120R.RN3P
 184-10168
 MK7.9A
 181-50840
 TWT2
 MCTPP120R
 MBT14SFC
 E4500
 TSRI-JB2
 309-65110
 309-65110
 309-65129

 65129
 309-65214
 309-65208
 309-65117
 309-65118
 309-65164
 NGM20-RED
 NGM32-DGY
 GSS3
 321-50012
 H75X25

 BLACK 500
 HIS-3-9/3-PEX-CL
 HISA-18/6-PEX-CL
 HGDC2-5BW/1
 HELADUCT
 FLEX30
 SK
 T50RS5.NB3P
 T30LR