


Specification Sheet

Part Number: REZ300.NB3P



Releasable Cable Tie, 12" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg

Article Number 115-40300

Type REZ300

Color Black (BK)

Features & Benefits

- The unique, patented head design enables the tie to be inserted through a standard style head for permanent locking or can be twisted into the pinch-releasable style head for easy opening at a later time.
- The quick pinch-release mechanism can be released by one hand even when the tie is under tension.

Quantity Per bag

Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Releasable Cable Tie, 12" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg
Global Part Name	REZ300-PA66-BK
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135
Length L (Imperial)	12.0
Length L (Metric)	305
Identification Plate Position	none
Releasable Closure	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.63

Bundle Diameter Min (Metric)	16.0
Bundle Diameter Max (Imperial)	3.2
Bundle Diameter Max (Metric)	80.0
Thickness T (Imperial)	0.055
Thickness T (Metric)	1.4
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

Content Unit(BMEcat) pcs.

Weight (Metric) 2.29

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hellermann](#) manufacturer:

Other Similar products are found below :

[T18RPOCKETPAC](#) [380-03003](#) [406064A](#) [TSR1I-21](#) [TSR1I-29](#) [TSR1I-33](#) [TSR1I-36](#) [105-4JW8](#) [MS3109-12AU](#) [Q30LR-PA66-BK-C1](#) [Q18I-PA66-NA-C1](#) [Q18R-PA66-NA-C1](#) [CTQM5-PA66-BK-C1](#) [308-10600](#) [T50IDH0C2](#) [AS25](#) [T18MR-NAT\(100 PACK\)](#) [T120L.NN2P](#) [MK7.9A](#) [181-50840](#) [621-10405](#) [164-21008](#) [TWT2](#) [G51P-A-PE-NA](#) [E4500](#) [GT.50X66P2](#) [TSRI-JB2](#) [111-01626](#) [SBS4 NATURAL](#) [SBPEFR4-PE-BK-30M](#) [308-30421](#) [309-65129](#) [309-65213](#) [309-65298](#) [309-65164](#) [HIS-3-9/3-PEX-BU](#) [HIS-3 6/2 BRN](#) [HGDC1-3CC/7](#) [HEGPA6612 GREY](#) [T50RS5.NB3P](#) [T150M-NAT](#) [HGDC1-3BW/3](#) [HG1-3](#) [HIS-3 3/1 BLU](#) [HGDC2-5BW/N](#) [HGDC2-5BW/L](#) [TSR1I-25](#) [RSB3](#) [RT250XL9X2](#) [SLHD3X2G4](#)