## **HellermannTyton**

## **Specification Sheet**

Part Number: SNP610C2

**Quantity Per** 



Snapper Hose Clamp, .45"-.51" Bundle Diameter, POM, White, 100/pkg

| Article Number      | 190-00187   |
|---------------------|---|
| Туре                | SNP6  |
| Color               | White (WH)  |
| Features & Benefits | <ul> <li>Designed for quick, ratcheted installation and can be released and<br/>reused.</li> <li>Polyacetal material resists chemicals, corrosion and UV<br/>rays making it suitable for extreme environments.</li> </ul> |

bag

| _        |    |    | - 4 | _     |       | 4 .   |
|----------|----|----|-----|-------|-------|-------|
| <b>D</b> | rn | du | C+  | I IAC | crin  | tion  |
|          |    | uu | U.  |       | OI ID | LIVII |

Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.

**Short Description** 

Snapper Hose Clamp, .45"-.51" Bundle Diameter, POM, White, 100/pkg

**Global Part Name** 

SNP6-POM-WH

**Fixation Method** 

Plug-in mounting

**Variant** 

Closed

**Bundle Diameter Min (Imperial)** 

0.47

**Bundle Diameter Min (Metric)** 

12.0

**Bundle Diameter Max (Imperial)** 

0.54

**Bundle Diameter Max (Metric)** 

13.7

Wall Thickness WT (Imperial)

.069

Wall Thickness WT (Metric)

1.8

Material Polyacetal (POM)

Material Shortcut POM

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature (Metric) -40°F to +194°F (-40°C to +90°C)

ROHS Complaint Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

**Customs Number** 3926909988

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hellermann manufacturer:

Other Similar products are found below:

T18RPOCKETPAC 380-03003 406064A TSR1I-21 TSR1I-29 TSR1I-33 TSR1I-36 105-4JW8 MS3109-12AU Q30LR-PA66-BK-C1 Q18I-PA66-NA-C1 Q18R-PA66-NA-C1 CTQM5-PA66-BK-C1 308-10600 T50IDH0C2 AS25 T18MR-NAT(100 PACK) T120L.NN2P MK7.9A 181-50840 621-10405 164-21008 TWT2 G51P-A-PE-NA E4500 GT.50X66P2 TSRI-JB2 111-01626 SBS4 NATURAL SBPEFR4-PE-BK-30M 308-30421 309-65129 309-65213 309-65298 309-65164 HIS-3-9/3-PEX-BU HIS-3 6/2 BRN HGDC1-3CC/7 HEGPA6612 GREY T50RS5.NB3P T150M-NAT HGDC1-3BW/3 HG1-3 HIS-3 3/1 BLU HGDC2-5BW/N HGDC2-5BW/L TSR1I-25 RSB3 RT250XL9X2 SLHD3X2G4