


## Specification Sheet

Part Number: T40I9M4



Cable Tie, 11" Long, UL Rated, 40lb Tensile Strength, PA66, Natural, 1000/pkg

**Article Number** 111-04612

**Type** T40I

**Color** Natural (NA)

**Features & Benefits**

- Engineered and manufactured for maximum performance and quality.
- Made from 100% high-quality plastic to ensure efficient recycling.
- Inside serration for a strong grip onto bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail allows for simpler insertion.

**Quantity Per** bag

<b>Product Description</b>	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Cable Tie, 11" Long, UL Rated, 40lb Tensile Strength, PA66, Natural, 1000/pkg
<b>Global Part Name</b>	T40I-PA66-NA
<b>Minimum Tensile Strength (Imperial)</b>	40.0
<b>Minimum Tensile Strength (Metric)</b>	180.0
<b>Length L (Imperial)</b>	11.0
<b>Length L (Metric)</b>	295.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.16
<b>Width W (Metric)</b>	4.0
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5

<b>Bundle Diameter Max (Imperial)</b>	3.15
<b>Bundle Diameter Max (Metric)</b>	80.0
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>UL Listed (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	1000

**Package Quantity (Metric)**

1000

**Customs Number**

3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Hellermann](#) manufacturer:*

Other Similar products are found below :

[T18RPOCKETPAC](#) [380-03003](#) [406064A](#) [TSR1I-21](#) [TSR1I-29](#) [TSR1I-33](#) [TSR1I-36](#) [105-4JW8](#) [MS3109-12AU](#) [Q30LR-PA66-BK-C1](#) [Q18I-PA66-NA-C1](#) [Q18R-PA66-NA-C1](#) [CTQM5-PA66-BK-C1](#) [308-10600](#) [T50IDH0C2](#) [AS25](#) [T18MR-NAT\(100 PACK\)](#) [T120L.NN2P](#) [MK7.9A](#) [181-50840](#) [621-10405](#) [164-21008](#) [TWT2](#) [G51P-A-PE-NA](#) [E4500](#) [GT.50X66P2](#) [TSRI-JB2](#) [111-01626](#) [SBS4 NATURAL](#) [SBPEFR4-PE-BK-30M](#) [308-30421](#) [309-65129](#) [309-65213](#) [309-65298](#) [309-65164](#) [HIS-3-9/3-PEX-BU](#) [HIS-3 6/2 BRN](#) [HGDC1-3CC/7](#) [HEGPA6612 GREY](#) [T50RS5.NB3P](#) [T150M-NAT](#) [HGDC1-3BW/3](#) [HG1-3](#) [HIS-3 3/1 BLU](#) [HGDC2-5BW/N](#) [HGDC2-5BW/L](#) [TSR1I-25](#) [RSB3](#) [RT250XL9X2](#) [SLHD3X2G4](#)